




**P = 0.37 кВт**


50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
520	6.7	1.35	2.64	BG05-../D07LA4	11	420	-	620	5.6	1.6
400	8.8	1.15	3.38	"	"	460	-	480	7.3	1.35
295	11.9	1.0	4.59	"	"	490	-	355	9.9	1.2
250	14.1	0.99	5.46	"	"	490	-	300	11.7	1.2
205	17.2	0.93	6.60	"	"	510	-	250	14.1	1.15
174	20	0.9	7.80	"	"	530	-	210	16.8	1.05
166	21	0.86	8.15	"	"	510	-	199	17.7	1.0
159	22	0.86	8.51	"	"	550	-	191	18.5	1.05
360	9.8	2.0	3.78	BG06-../D07LA4	12	520	-	430	8.2	2.4
300	11.7	1.9	4.54	"	"	530	-	360	9.8	2.2
230	15.3	1.55	5.96	"	"	570	-	275	12.8	1.9
193	18.3	1.4	7.01	"	"	580	-	235	15	1.75
161	21.5	1.3	8.39	"	"	600	-	194	18.2	1.55
144	24.5	1.2	9.38	"	"	640	-	173	20	1.5
132	26.5	1.15	10.24	"	"	640	-	159	22	1.4
120	29	1.1	11.28	"	"	670	-	144	24.5	1.3
110	32	1.05	12.30	"	"	670	-	132	26.5	1.25
105	33.5	0.99	12.98	"	"	600	-	125	28	1.2
92	38	0.89	14.78	"	"	730	-	110	32	1.05
84	42	0.83	16.13	"	"	740	-	101	34.5	1.0
78	45	0.84	17.40	"	"	760	-	94	37.5	1.0
72	49	0.82	18.98	"	"	770	-	86	41	0.98
103	34	3.2	13.21	BG10-../D07LA4	15	1070	1490	123	28.5	3.9
93	37.5	3.0	14.58	"	"	1100	1540	112	31.5	3.6
84	42	2.8	16.15	"	"	1140	1590	101	34.5	3.4
73	48	2.5	18.51	"	"	1210	1690	88	40	3.0
66	53	2.3	20.51	"	"	1290	1800	79	44.5	2.7
62	56	2.1	22.04	"	"	1330	1860	74	47.5	2.5
56	63	1.9	24.42	"	"	1410	1970	67	52	2.3
52	67	1.8	26.26	"	"	1460	2000	62	56	2.1
46.5	75	1.6	29.09	"	"	1540	2150	56	63	1.9
43	82	1.45	31.52	"	"	1600	2200	52	67	1.8
39	90	1.35	34.92	"	"	1690	2350	46.5	75	1.6
34.5	102	1.2	39.70	"	"	1780	2450	41	86	1.4
31	113	1.05	43.99	"	"	1880	2600	37	95	1.25
29.5	119	1.0	46.55	"	"	1920	2650	35	100	1.2
26.5	133	0.9	51.57	"	"	2000	2800	31.5	112	1.05
23.5	150	0.8	57.48	"	"	2000	2800	28.5	123	0.98
53	66	3.0	25.79	BG20-../D07LA4	18	3700	-	63	56	3.6
48.5	72	2.8	27.85	"	"	3800	-	59	59	3.4
44	80	2.5	30.94	"	"	4000	-	53	66	3.0
41	86	2.3	33.33	"	"	4100	-	49	72	2.8
36.5	96	2.1	37.02	"	"	4300	-	44	80	2.5
32.5	108	1.85	41.76	"	"	4500	-	39	90	2.2
29.5	119	1.7	46.38	"	"	4700	-	35	100	2.0
28.5	123	1.65	47.92	"	"	4750	-	34	103	1.95
25.5	138	1.45	53.22	"	"	4950	-	30.5	115	1.75
23	153	1.3	59.07	"	"	5000	-	27.5	128	1.55
21	168	1.2	65.62	"	"	5000	-	25	141	1.4
20	176	1.15	67.53	BG20Z-../D07LA4	19	5000	-	24	147	1.35
17.5	200	1.0	78.60	"	"	5000	-	21	168	1.2
15.5	225	0.89	87.30	"	"	5000	-	19	185	1.1
14.5	240	0.83	94.27	"	"	5000	-	17.5	200	1.0
38.5	91	3.3	35.17	BG30-../D07LA4	22	5500	-	46.5	75	4.0
35	100	3.0	39.02	"	"	5800	-	42	84	3.6
32	110	2.7	42.46	"	"	5900	-	38.5	91	3.3
29	121	2.5	47.11	"	"	6000	-	34.5	102	2.9
26	135	2.2	52.44	"	"	6000	-	31	113	2.7
23.5	150	2.0	58.18	"	"	6000	-	28	126	2.4
22.5	157	1.9	60.79	"	"	6000	-	27	130	2.3
20.5	172	1.75	67.44	"	"	6000	-	24.5	144	2.1

**P = 0.37 кВт**




50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
18.5	191	1.55	73.51	BG30Z-../D07LA4	25	6000	-	22.5	157	1.9
17	205	1.45	81.55	"	"	6000	-	20	176	1.7
16	220	1.35	86.13	"	"	6000	-	19	185	1.6
14.5	240	1.25	95.55	"	"	6000	-	17	205	1.45
12.5	280	1.05	109.6	"	"	6000	-	15	235	1.3
11.5	305	0.98	121.6	"	"	6000	-	13.5	260	1.15
11	320	0.94	128.5	"	"	6000	-	13	270	1.1
9.5	370	0.81	142.5	"	"	6000	-	11.5	305	0.98
20	176	2.4	67.74	BG40Z-../D07LA4	40	7000	-	24	147	2.9
18	196	2.2	75.19	"	"	7000	-	22	160	2.7
16.5	210	2.0	82.00	"	"	7000	-	20	176	2.4
15	235	1.8	91.02	"	"	7000	-	18	196	2.2
14	250	1.7	96.86	"	"	7000	-	17	205	2.1
13	270	1.55	107.5	"	"	7000	-	15.5	225	1.9
11.5	305	1.4	121.3	"	"	7000	-	13.5	260	1.65
10.5	335	1.25	134.6	"	"	7000	-	12.5	280	1.5
9.6	365	1.15	141.4	"	"	7000	-	11.5	305	1.4
8.7	405	1.05	156.9	"	"	7000	-	10.5	335	1.25
8.2	430	0.99	166.1	"	"	7000	-	9.8	360	1.2
7.4	475	0.89	184.4	"	"	7000	-	8.8	400	1.05
6.8	510	0.83	199.9	"	"	7000	-	8.2	430	0.99
17	205	3.1	79.78	BG50Z-../D07LA4	50	10000	-	20.5	172	3.7
14.5	240	2.6	95.58	"	"	10000	-	17	205	3.1
13	270	2.3	106.0	"	"	10000	-	15.5	225	2.8
10.5	335	1.9	128.9	"	"	10000	-	13	270	2.3
9.5	370	1.7	142.9	"	"	10000	-	11.5	305	2.1
8.2	430	1.45	164.9	"	"	10000	-	9.9	355	1.75
7.4	475	1.35	182.8	"	"	10000	-	8.9	395	1.6
6.6	530	1.2	204.7	"	"	10000	-	8.0	440	1.45
6.0	580	1.1	226.9	"	"	10000	-	7.2	490	1.3
5.3	660	0.95	258.6	"	"	10000	-	6.3	560	1.15
4.8	730	0.86	286.7	"	"	10000	-	5.7	610	1.05
3.9	800	0.86	351.7	BG50G10-../D07LA4	54	10000	-	4.7	650	1.05
4.9	600	2.2	276.2	BG60G20-../D07LA4	102	16000	-	5.9	480	2.7
4.5	650	2.0	306.1	"	"	16000	-	5.3	530	2.5
4.1	720	1.8	334.3	"	"	16000	-	4.9	580	2.2
3.7	790	1.65	370.5	"	"	16000	-	4.4	640	2.0
3.1	970	1.35	437.3	"	"	16000	-	3.8	760	1.7
2.7	1160	1.1	504.9	"	"	16000	-	3.3	920	1.4
2.5	1240	1.05	559.5	"	"	16000	-	2.9	1050	1.25
2.1	1510	0.86	651.3	"	"	16000	-	2.5	1240	1.05
3.5	860	2.9	387.6	BG70G20-../D07LA4	132	20000	-	4.2	690	3.6
3.3	940	2.7	417.8	"	"	20000	-	3.9	780	3.2
2.8	1110	2.3	495.9	"	"	20000	-	3.3	920	2.7
2.4	1320	1.9	577.3	"	"	20000	-	2.9	1070	2.3
2.1	1510	1.65	665.8	"	"	20000	-	2.5	1240	2.0
1.8	1760	1.4	790.2	"	"	20000	-	2.1	1480	1.7
1.6	2000	1.25	877.6	"	"	20000	-	1.9	1650	1.5
1.4	2300	1.1	1035	"	"	20000	-	1.6	1980	1.25
1.2	2700	0.93	1193	"	"	20000	-	1.4	2250	1.1


**P = 0.55 кВт**


50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
500	10.5	1.7	2.82	<b>BG06-../D08MA4</b>	16	470	-	600	8.7	2.1
375	14	1.45	3.78	"	"	520	-	445	11.8	1.7
310	16.9	1.3	4.54	"	"	530	-	375	14	1.55
235	22	1.1	5.96	"	"	570	-	285	18.4	1.3
200	26	1.0	7.01	"	"	580	-	240	21.5	1.2
167	31	0.9	8.39	"	"	600	-	205	25.5	1.1
150	35	0.86	9.38	"	"	640	-	180	29	1.05
137	38	0.82	10.24	"	"	640	-	165	31.5	0.98
210	25	3.2	6.78	<b>BG10-../D08MA4</b>	16	660	920	250	21	3.9
174	30	2.9	8.07	"	"	660	920	210	25	3.5
151	34.5	2.8	9.33	"	"	950	1330	181	29	3.3
136	38.5	2.6	10.34	"	"	1000	1400	163	32	3.1
118	44.5	2.4	11.92	"	"	1030	1440	141	37	2.8
106	49.5	2.2	13.21	"	"	1070	1490	128	41	2.7
97	54	2.1	14.58	"	"	1100	1540	116	45	2.5
87	60	1.95	16.15	"	"	1140	1590	105	50	2.3
76	69	1.75	18.51	"	"	1210	1690	91	57	2.1
69	76	1.6	20.51	"	"	1290	1800	82	64	1.9
64	82	1.45	22.04	"	"	1330	1860	77	68	1.75
58	90	1.35	24.42	"	"	1410	1970	69	76	1.6
54	97	1.25	26.26	"	"	1460	2000	64	82	1.45
48.5	108	1.1	29.09	"	"	1540	2150	58	90	1.35
44.5	118	1.0	31.52	"	"	1600	2200	54	97	1.25
40.5	129	0.93	34.92	"	"	1690	2350	48.5	108	1.1
35.5	147	0.82	39.70	"	"	1780	2450	42.5	123	0.98
96	54	3.2	14.67	<b>BG20-../D08MA4</b>	19	3050	-	115	45.5	3.8
90	58	3.1	15.58	"	"	3100	-	108	48.5	3.6
81	64	2.9	17.31	"	"	3200	-	98	53	3.5
71	73	2.7	19.95	"	"	3350	-	85	61	3.2
64	82	2.4	22.16	"	"	3500	-	76	69	2.9
61	86	2.3	23.22	"	"	3550	-	73	71	2.8
55	95	2.1	25.79	"	"	3700	-	66	79	2.5
51	102	1.95	27.85	"	"	3800	-	61	86	2.3
45.5	115	1.75	30.94	"	"	4000	-	55	95	2.1
42.5	123	1.65	33.33	"	"	4100	-	51	102	1.95
38	138	1.45	37.02	"	"	4300	-	45.5	115	1.75
34	154	1.3	41.76	"	"	4500	-	40.5	129	1.55
30.5	172	1.15	46.38	"	"	4700	-	36.5	143	1.4
29.5	178	1.1	47.92	"	"	4750	-	35.5	147	1.35
26.5	198	1.0	53.22	"	"	4950	-	32	164	1.2
24	215	0.93	59.07	"	"	5000	-	28.5	184	1.1
21.5	240	0.83	65.62	"	"	5000	-	26	200	1.0
21	250	0.8	67.53	<b>BG20Z-../D08MA4</b>	20	5000	-	25	210	0.95
56	93	3.2	25.45	<b>BG30-../D08MA4</b>	23	4850	-	67	78	3.8
50	105	2.9	28.24	"	"	5100	-	60	87	3.4
47	111	2.7	29.83	"	"	5200	-	57	92	3.3
42.5	123	2.4	33.09	"	"	5400	-	51	102	2.9
40	131	2.3	35.17	"	"	5500	-	48	109	2.8
36	145	2.1	39.02	"	"	5800	-	43.5	120	2.5
33	159	1.9	42.46	"	"	5900	-	40	131	2.3
30	175	1.7	47.11	"	"	6000	-	36	145	2.1
27	194	1.55	52.44	"	"	6000	-	32.5	161	1.85
24.5	210	1.45	58.18	"	"	6000	-	29	181	1.65
23.5	220	1.35	60.79	"	"	6000	-	28	187	1.6
21	250	1.2	67.44	"	"	6000	-	25	210	1.45
19.5	265	1.15	73.51	<b>BG30Z-../D08MA4</b>	26	6000	-	23	225	1.35
17.5	300	1.0	81.55	"	"	6000	-	21	250	1.2
16.5	315	0.95	86.13	"	"	6000	-	20	260	1.15
15	350	0.86	95.55	"	"	6000	-	18	290	1.05

**P = 0.55 кВт**



50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
41	128	3.3	34.20	BG40-../D08MA4	38	7000	-	49.5	106	4.0
37	141	3.0	37.96	"	"	7000	-	44.5	118	3.6
35	150	2.8	40.19	"	"	7000	-	42	125	3.4
31.5	166	2.6	44.62	"	"	7000	-	38	138	3.1
29	181	2.3	48.36	"	"	7000	-	35	150	2.8
26.5	198	2.1	53.69	"	"	7000	-	31.5	166	2.6
23.5	220	1.95	59.64	"	"	7000	-	28.5	184	2.3
21.5	240	1.75	66.20	"	"	7000	-	25.5	205	2.1
21	250	1.7	67.74	BG40Z-../D08MA4	42	7000	-	25	210	2.0
19	275	1.55	75.19	"	"	7000	-	22.5	230	1.85
17.5	300	1.4	82.00	"	"	7000	-	20.5	255	1.65
15.5	335	1.25	91.02	"	"	7000	-	18.5	280	1.5
14.5	360	1.2	96.86	"	"	7000	-	17.5	300	1.4
13.5	385	1.1	107.5	"	"	7000	-	16	325	1.3
12	435	0.98	121.3	"	"	7000	-	14	375	1.15
10.5	500	0.85	134.6	"	"	7000	-	12.5	420	1.0
10	520	0.82	141.4	"	"	7000	-	12	435	0.98
:										
27	194	3.2	52.12	BG50-../D08MA4	46	10000	-	32.5	161	3.9
24	215	2.9	59.42	"	"	10000	-	28.5	184	3.4
21.5	240	2.6	65.86	"	"	10000	-	26	200	3.2
19.5	265	2.4	71.97	BG50Z-../D08MA4	51	10000	-	23.5	220	2.9
18	290	2.2	79.78	"	"	10000	-	21.5	240	2.6
15	350	1.8	95.58	"	"	10000	-	18	290	2.2
13.5	385	1.65	106.0	"	"	10000	-	16	325	1.95
11	475	1.35	128.9	"	"	10000	-	13.5	385	1.65
9.8	530	1.2	142.9	"	"	10000	-	12	435	1.45
8.5	610	1.05	164.9	"	"	10000	-	10.5	500	1.25
7.7	680	0.93	182.8	"	"	10000	-	9.2	570	1.1
6.9	760	0.83	204.7	"	"	10000	-	8.3	630	1.0
:										
14	375	3.2	101.0	BG60Z-../D08MA4	96	16000	-	17	305	3.9
12	435	2.8	119.2	"	"	16000	-	14.5	360	3.3
11	475	2.5	132.1	"	"	16000	-	13	400	3.0
8.9	590	2.0	158.0	"	"	16000	-	11	475	2.5
8.0	650	1.85	175.1	"	"	16000	-	9.6	540	2.2
6.9	760	1.6	204.6	"	"	16000	-	8.3	630	1.9
6.2	840	1.45	226.7	"	"	16000	-	7.5	700	1.7
5.7	920	1.3	247.7	"	"	16000	-	6.8	770	1.55
5.2	1010	1.2	274.5	"	"	16000	-	6.2	840	1.45
5.1	910	1.45	276.2	BG60G20-../D08MA4	103	16000	-	6.1	740	1.75
4.6	1010	1.3	306.1	"	"	16000	-	5.5	820	1.6
4.2	1110	1.15	334.3	"	"	16000	-	5.1	880	1.5
3.8	1220	1.05	370.5	"	"	16000	-	4.6	980	1.35
3.3	1420	0.92	437.3	"	"	16000	-	3.9	1180	1.1
:										
7.3	710	3.2	194.4	BG70Z-../D08MA4	136	20000	-	8.7	600	3.8
6.7	780	2.9	210.5	"	"	20000	-	8.0	650	3.5
5.7	920	2.5	249.8	"	"	20000	-	6.8	770	3.0
5.5	840	3.0	255.5	BG70G20-../D08MA4	133	20000	-	6.6	680	3.7
5.1	910	2.7	276.7	"	"	20000	-	6.1	740	3.4
4.3	1080	2.3	328.4	"	"	20000	-	5.2	870	2.9
3.7	1270	1.95	387.6	"	"	20000	-	4.4	1040	2.4
3.4	1420	1.75	417.8	"	"	20000	-	4.1	1150	2.2
2.9	1660	1.5	495.9	"	"	20000	-	3.4	1390	1.8
2.5	1950	1.3	577.3	"	"	20000	-	3.0	1600	1.55
2.2	2200	1.15	665.8	"	"	20000	-	2.6	1850	1.35
1.8	2700	0.93	790.2	"	"	20000	-	2.2	2150	1.15
1.6	3050	0.82	877.6	"	"	20000	-	2.0	2400	1.05
:										
2.9	1430	3.2	484.3	BG80G40-../D08MA4	215	26000	-	3.5	1120	4.1
2.5	1720	2.7	572.0	"	"	26000	-	3.0	1370	3.4
2.2	1900	2.4	657.8	"	"	26000	-	2.6	1540	3.0
2.0	2100	2.2	730.3	"	"	26000	-	2.4	1690	2.7
1.8	2350	1.95	817.4	"	"	26000	-	2.1	1970	2.3
1.6	2700	1.7	907.6	"	"	26000	-	1.9	2200	2.1


**P = 0.55 кВт**


50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
1.4	3200	1.45	1042	BG80G40-../D08MA4	"	26000	-	1.7	2500	1.85
1.2	3800	1.2	1261	"	"	26000	-	1.4	3200	1.45
1.0	4700	0.98	1400	"	"	26000	-	1.2	3800	1.2
1.2	3700	2.5	1174	BG90G50-../D08MA4	324	65000	-	1.5	2800	3.3
1.1	4100	2.2	1301	"	"	65000	-	1.3	3350	2.7
0.9	5100	1.8	1583	"	"	65000	-	1.1	4100	2.2
0.8	5800	1.6	1756	"	"	65000	-	1.0	4550	2.0
0.7	6800	1.35	2026	"	"	65000	-	0.85	5500	1.65
0.6	8000	1.15	2514	"	"	65000	-	0.7	6800	1.35
0.55	8800	1.05	2786	"	"	65000	-	0.65	7400	1.25
0.65	6000	3.1	2154	BG100G50-../D08MA4	512	90000	-	0.8	4500	4.1
0.55	7100	2.6	2656	"	"	90000	-	0.65	5700	3.2
0.48	8600	2.2	2952	"	"	90000	-	0.6	6500	2.8
0.43	9700	1.9	3286	"	"	90000	-	0.55	7000	2.6
0.39	10900	1.7	3644	"	"	90000	-	0.47	8600	2.2
0.33	13400	1.4	4366	"	"	90000	-	0.39	10900	1.7
0.29	15600	1.2	4839	"	"	90000	-	0.35	12500	1.5

**P = 0.75 кВт**


50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
500	14.3	1.25	2.82	BG06-../D08LA4	18	470	-	600	11.9	1.5
375	19.1	1.05	3.78	"	"	520	-	445	16	1.25
310	23	0.96	4.54	"	"	530	-	375	19.1	1.15
235	30	0.8	5.96	"	"	570	-	285	25	0.96
325	22	3.1	4.36	BG10-../D08LA4	18	650	910	390	18.3	3.7
265	27	2.8	5.34	"	"	620	910	315	22.5	3.3
210	34	2.4	6.78	"	"	660	920	250	28.5	2.8
174	41	2.1	8.07	"	"	660	920	210	34	2.6
151	47	2.1	9.33	"	"	950	1330	181	39.5	2.5
136	52	1.9	10.34	"	"	1000	1400	163	43.5	2.3
118	60	1.75	11.92	"	"	1030	1440	141	50	2.1
106	67	1.65	13.21	"	"	1070	1490	128	55	2.0
97	73	1.55	14.58	"	"	1100	1540	116	61	1.85
87	82	1.45	16.15	"	"	1140	1590	105	68	1.7
76	94	1.3	18.51	"	"	1210	1690	91	78	1.55
69	103	1.15	20.51	"	"	1290	1800	82	87	1.4
64	111	1.1	22.04	"	"	1330	1860	77	93	1.3
58	123	0.98	24.42	"	"	1410	1970	69	103	1.15
54	132	0.91	26.26	"	"	1460	2000	64	111	1.1
48.5	147	0.82	29.09	"	"	1540	2150	58	123	0.98
169	42	2.9	8.29	BG20-../D08LA4	20	2250	-	205	34.5	3.5
158	45	3.2	8.91	"	"	2600	-	189	37.5	3.8
146	49	2.5	9.65	"	"	2250	-	175	40.5	3.0
133	53	2.9	10.54	"	"	2700	-	160	44.5	3.5
120	59	2.7	11.71	"	"	2800	-	144	49.5	3.2
106	67	2.5	13.21	"	"	2900	-	128	55	3.0
96	74	2.3	14.67	"	"	3050	-	115	62	2.8
90	79	2.2	15.58	"	"	3100	-	108	66	2.7
81	88	2.1	17.31	"	"	3200	-	98	73	2.5
71	100	1.95	19.95	"	"	3350	-	85	84	2.3
64	111	1.8	22.16	"	"	3500	-	76	94	2.1
61	117	1.7	23.22	"	"	3550	-	73	98	2.0
55	130	1.55	25.79	"	"	3700	-	66	108	1.85
51	140	1.45	27.85	"	"	3800	-	61	117	1.7
45.5	157	1.25	30.94	"	"	4000	-	55	130	1.55
42.5	168	1.2	33.33	"	"	4100	-	51	140	1.45
38	188	1.05	37.02	"	"	4300	-	45.5	157	1.25

**P = 0.75 кВт**



50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
34	210	0.95	41.76	BG20-../D08LA4	"	4500	-	40.5	176	1.15
30.5	230	0.87	46.38	"	"	4700	-	36.5	196	1.0
29.5	240	0.83	47.92	"	"	4750	-	35.5	200	1.0
74	96	3.1	18.93	BG30-../D08LA4	25	4100	-	89	80	3.8
71	100	3.0	19.99	"	"	4200	-	85	84	3.6
64	111	2.7	22.18	"	"	4600	-	76	94	3.2
56	127	2.4	25.45	"	"	4850	-	67	106	2.8
50	143	2.1	28.24	"	"	5100	-	60	119	2.5
47	152	1.95	29.83	"	"	5200	-	57	125	2.4
42.5	168	1.8	33.09	"	"	5400	-	51	140	2.1
40	179	1.7	35.17	"	"	5500	-	48	149	2.0
36	198	1.5	39.02	"	"	5800	-	43.5	164	1.85
33	215	1.4	42.46	"	"	5900	-	40	179	1.7
30	235	1.3	47.11	"	"	6000	-	36	198	1.5
27	265	1.15	52.44	"	"	6000	-	32.5	220	1.35
24.5	290	1.05	58.18	"	"	6000	-	29	245	1.2
23.5	300	1.0	60.79	"	"	6000	-	28	255	1.2
21	340	0.88	67.44	"	"	6000	-	25	285	1.05
19.5	365	0.82	73.51	BG30Z-../D08LA4	28	6000	-	23	310	0.97
54	132	3.2	26.01	BG40-../D08LA4	40	6500	-	65	110	3.9
48	149	2.9	29.34	"	"	6800	-	58	123	3.5
43	166	2.6	32.57	"	"	7000	-	52	137	3.1
41	174	2.4	34.20	"	"	7000	-	49.5	144	3.0
37	193	2.2	37.96	"	"	7000	-	44.5	160	2.7
35	200	2.1	40.19	"	"	7000	-	42	170	2.5
31.5	225	1.9	44.62	"	"	7000	-	38	188	2.3
29	245	1.75	48.36	"	"	7000	-	35	200	2.1
26.5	270	1.55	53.69	"	"	7000	-	31.5	225	1.9
23.5	300	1.4	59.64	"	"	7000	-	28.5	250	1.7
21.5	330	1.3	66.20	"	"	7000	-	25.5	280	1.5
21	340	1.25	67.74	BG40Z-../D08LA4	43	7000	-	25	285	1.5
19	375	1.15	75.19	"	"	7000	-	22.5	315	1.35
17.5	405	1.05	82.00	"	"	7000	-	20.5	345	1.25
15.5	460	0.92	91.02	"	"	7000	-	18.5	385	1.1
14.5	490	0.87	96.86	"	"	7000	-	17.5	405	1.05
13.5	530	0.8	107.5	"	"	7000	-	16	445	0.96
37	193	3.3	37.89	BG50-../D08LA4	48	10000	-	44.5	160	3.9
33.5	210	3.0	42.00	"	"	10000	-	40	179	3.5
30	235	2.7	47.02	"	"	10000	-	36	198	3.2
27	265	2.4	52.12	"	"	10000	-	32.5	220	2.9
24	295	2.1	59.42	"	"	10000	-	28.5	250	2.5
21.5	330	1.9	65.86	"	"	10000	-	26	275	2.3
19.5	365	1.75	71.97	BG50Z-../D08LA4	52	10000	-	23.5	300	2.1
18	395	1.6	79.78	"	"	10000	-	21.5	330	1.9
15	475	1.35	95.58	"	"	10000	-	18	395	1.6
13.5	530	1.2	106.0	"	"	10000	-	16	445	1.4
11	650	0.97	128.9	"	"	10000	-	13.5	530	1.2
9.8	730	0.86	142.9	"	"	10000	-	12	590	1.05
18.5	385	3.1	75.71	BG60Z-../D08LA4	97	16000	-	22.5	315	3.8
15.5	460	2.6	91.09	"	"	16000	-	18.5	385	3.1
14	510	2.4	101.0	"	"	16000	-	17	420	2.9
12	590	2.0	119.2	"	"	16000	-	14.5	490	2.4
11	650	1.85	132.1	"	"	16000	-	13	550	2.2
8.9	800	1.5	158.0	"	"	16000	-	11	650	1.85
8.0	890	1.35	175.1	"	"	16000	-	9.6	740	1.6
6.9	1030	1.15	204.6	"	"	16000	-	8.3	860	1.4
6.2	1150	1.05	226.7	"	"	16000	-	7.5	950	1.25
5.7	1250	0.96	247.7	"	"	16000	-	6.8	1050	1.15
5.2	1370	0.88	274.5	"	"	16000	-	6.2	1150	1.05
5.1	1280	1.0	276.2	BG60G20-../D08LA4	105	16000	-	6.1	1050	1.25
4.6	1420	0.92	306.1	"	"	16000	-	5.5	1170	1.1
4.2	1560	0.83	334.3	"	"	16000	-	5.1	1260	1.05




**P = 0.75 кВт**


50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
9.6	740	3.1	147.2	BG70Z-../D08LA4	137	20000	-	11.5	620	3.7
8.6	830	2.8	163.8	"	"	20000	-	10.5	680	3.4
7.3	980	2.3	194.4	"	"	20000	-	8.7	820	2.8
6.7	1060	2.2	210.5	"	"	20000	-	8.0	890	2.6
5.7	1250	1.85	249.8	"	"	20000	-	6.8	1050	2.2
5.5	1190	2.1	255.5	BG70G20-../D08LA4	135	20000	-	6.6	970	2.6
5.1	1280	1.95	276.7	"	"	20000	-	6.1	1050	2.4
4.3	1520	1.65	328.4	"	"	20000	-	5.2	1230	2.0
3.7	1780	1.4	387.6	"	"	20000	-	4.4	1480	1.7
3.4	1980	1.25	417.8	"	"	20000	-	4.1	1620	1.55
2.9	2300	1.1	495.9	"	"	20000	-	3.4	1960	1.3
2.5	2700	0.93	577.3	"	"	20000	-	3.0	2200	1.15
2.2	3050	0.82	665.8	"	"	20000	-	2.6	2550	0.98
3.9	1490	3.1	360.0	BG80G40-../D08LA4	216	26000	-	4.7	1180	3.9
3.6	1610	2.9	399.8	"	"	26000	-	4.3	1290	3.6
3.3	1830	2.5	436.2	"	"	26000	-	3.9	1490	3.1
2.9	2050	2.2	484.3	"	"	26000	-	3.5	1670	2.8
2.5	2450	1.9	572.0	"	"	26000	-	3.0	2000	2.3
2.2	2750	1.65	657.8	"	"	26000	-	2.6	2250	2.0
2.0	3050	1.5	730.3	"	"	26000	-	2.4	2450	1.9
1.8	3450	1.35	817.4	"	"	26000	-	2.1	2850	1.6
1.6	3900	1.2	907.6	"	"	26000	-	1.9	3200	1.45
1.4	4550	1.0	1042	"	"	26000	-	1.7	3650	1.25
1.2	5400	0.85	1261	"	"	26000	-	1.4	4550	1.0
2.0	2900	3.2	714.2	BG90G50-../D08LA4	326	65000	-	2.4	2300	4.0
1.6	3800	2.4	883.7	"	"	65000	-	2.0	2900	3.2
1.2	5200	1.75	1174	"	"	65000	-	1.5	4100	2.2
1.1	5800	1.6	1301	"	"	65000	-	1.3	4800	1.9
0.9	7200	1.3	1583	"	"	65000	-	1.1	5800	1.6
0.8	8200	1.1	1756	"	"	65000	-	1.0	6400	1.45
1.0	5700	3.2	1444	BG100G50-../D08LA4	513	90000	-	1.2	4550	4.1
0.85	6800	2.7	1678	"	"	90000	-	1.1	4900	3.8
0.75	7700	2.4	1867	"	"	90000	-	0.9	6100	3.0
0.65	8900	2.1	2154	"	"	90000	-	0.8	6800	2.7
0.55	10600	1.75	2656	"	"	90000	-	0.65	8600	2.2
0.48	12600	1.45	2952	"	"	90000	-	0.6	9600	1.95
0.43	14100	1.3	3286	"	"	90000	-	0.55	10500	1.75
0.39	15800	1.15	3644	"	"	90000	-	0.47	12700	1.45

**P = 1.1 кВт**


50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
560	18.7	3.0	2.52	BG10-../D09SA4	22	560	790	670	15.6	3.6
410	25.5	2.4	3.42	"	"	630	880	495	21	3.0
325	32	2.1	4.36	"	"	650	910	390	26.5	2.6
265	39.5	1.9	5.34	"	"	620	910	315	33	2.3
210	50	1.6	6.78	"	"	660	920	250	42	1.95
174	60	1.45	8.07	"	"	660	920	210	50	1.75
151	69	1.4	9.33	"	"	950	1330	181	58	1.65
136	77	1.3	10.34	"	"	1000	1400	163	64	1.55
118	89	1.2	11.92	"	"	1030	1440	141	74	1.4
106	99	1.1	13.21	"	"	1070	1490	128	82	1.35
97	108	1.05	14.58	"	"	1100	1540	116	90	1.25
87	120	0.98	16.15	"	"	1140	1590	105	100	1.15
76	138	0.87	18.51	"	"	1210	1690	91	115	1.05
320	32.5	3.2	4.38	BG20-../D09SA4	24	1990	-	385	27	3.9
260	40	2.9	5.49	"	"	2100	-	310	33.5	3.4
220	47.5	2.6	6.48	"	"	2250	-	260	40	3.1

**P = 1.1 кВт**



50 Гц			i	Тип	m кг	F <sub>RN</sub> Н	F <sub>RV</sub> Н	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
175	60	2.3	8.02	BG20-../D09SA4	"	2500	-	210	50	2.7
169	62	1.95	8.29	"	"	2250	-	205	51	2.4
158	66	2.2	8.91	"	"	2600	-	189	55	2.6
146	71	1.7	9.65	"	"	2250	-	175	60	2.0
133	78	1.95	10.54	"	"	2700	-	160	65	2.4
120	87	1.8	11.71	"	"	2800	-	144	72	2.2
106	99	1.7	13.21	"	"	2900	-	128	82	2.0
96	109	1.6	14.67	"	"	3050	-	115	91	1.9
90	116	1.55	15.58	"	"	3100	-	108	97	1.8
81	129	1.4	17.31	"	"	3200	-	98	107	1.7
71	147	1.35	19.95	"	"	3350	-	85	123	1.6
64	164	1.2	22.16	"	"	3500	-	76	138	1.45
61	172	1.15	23.22	"	"	3550	-	73	143	1.4
55	191	1.05	25.79	"	"	3700	-	66	159	1.25
51	205	0.98	27.85	"	"	3800	-	61	172	1.15
45.5	230	0.87	30.94	"	"	4000	-	55	191	1.05
42.5	245	0.82	33.33	"	"	4100	-	51	205	0.98
119	88	3.1	11.82	BG30-../D09SA4	29	3200	-	143	73	3.8
102	102	2.9	13.77	"	"	3150	-	123	85	3.5
92	114	2.6	15.27	"	"	3450	-	111	94	3.2
83	126	2.4	17.06	"	"	3700	-	99	106	2.8
74	141	2.1	18.93	"	"	4100	-	89	118	2.5
71	147	2.0	19.99	"	"	4200	-	85	123	2.4
64	164	1.85	22.18	"	"	4600	-	76	138	2.2
56	187	1.6	25.45	"	"	4850	-	67	156	1.9
50	210	1.45	28.24	"	"	5100	-	60	175	1.7
47	220	1.35	29.83	"	"	5200	-	57	184	1.65
42.5	245	1.2	33.09	"	"	5400	-	51	205	1.45
40	260	1.15	35.17	"	"	5500	-	48	215	1.4
36	290	1.05	39.02	"	"	5800	-	43.5	240	1.25
33	315	0.95	42.46	"	"	5900	-	40	260	1.15
30	350	0.86	47.11	"	"	6000	-	36	290	1.05
77	136	3.1	18.19	BG40-../D09SA4	43	5600	-	93	112	3.8
71	147	2.9	19.84	"	"	5800	-	85	123	3.5
64	164	2.6	22.02	"	"	6000	-	77	136	3.1
60	175	2.4	23.43	"	"	6200	-	72	145	2.9
54	194	2.2	26.01	"	"	6500	-	65	161	2.6
48	215	2.0	29.34	"	"	6800	-	58	181	2.3
43	240	1.75	32.57	"	"	7000	-	52	200	2.1
41	255	1.65	34.20	"	"	7000	-	49.5	210	2.0
37	280	1.5	37.96	"	"	7000	-	44.5	235	1.8
35	300	1.4	40.19	"	"	7000	-	42	250	1.7
31.5	330	1.3	44.62	"	"	7000	-	38	275	1.55
29	360	1.2	48.36	"	"	7000	-	35	300	1.4
26.5	395	1.1	53.69	"	"	7000	-	31.5	330	1.3
23.5	445	0.96	59.64	"	"	7000	-	28.5	365	1.15
21.5	485	0.88	66.20	"	"	7000	-	25.5	410	1.05
21	500	0.85	67.74	BG40Z-../D09SA4	47	7000	-	25	420	1.0
47.5	220	2.9	29.62	BG50-../D09SA4	51	8000	-	57	184	3.4
43	240	2.6	32.84	"	"	8700	-	52	200	3.2
37	280	2.3	37.89	"	"	10000	-	44.5	235	2.7
33.5	310	2.0	42.00	"	"	10000	-	40	260	2.4
30	350	1.8	47.02	"	"	10000	-	36	290	2.2
27	385	1.65	52.12	"	"	10000	-	32.5	320	1.95
24	435	1.45	59.42	"	"	10000	-	28.5	365	1.75
21.5	485	1.3	65.86	"	"	10000	-	26	400	1.6
19.5	530	1.2	71.97	BG50Z-../D09SA4	56	10000	-	23.5	445	1.4
18	580	1.1	79.78	"	"	10000	-	21.5	485	1.3
15	700	0.9	95.58	"	"	10000	-	18	580	1.1
13.5	770	0.82	106.0	"	"	10000	-	16	650	0.97
28	375	3.2	50.31	BG60-../D09SA4	82	16000	-	33.5	310	3.9
25.5	410	2.9	55.76	"	"	16000	-	30.5	340	3.5




**P = 1.1 кВт**


50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
23	455	2.6	60.90	BG60-../D09SA4	"	16000	-	28	375	3.2
21	500	2.4	67.49	"	"	16000	-	25	420	2.9
20.5	510	2.4	68.32	BG60Z-../D09SA4	101	16000	-	25	420	2.9
18.5	560	2.1	75.71	"	"	16000	-	22.5	465	2.6
15.5	670	1.8	91.09	"	"	16000	-	18.5	560	2.1
14	750	1.6	101.0	"	"	16000	-	17	610	1.95
12	870	1.4	119.2	"	"	16000	-	14.5	720	1.65
11	950	1.25	132.1	"	"	16000	-	13	800	1.5
8.9	1180	1.0	158.0	"	"	16000	-	11	950	1.25
8.0	1310	0.92	175.1	"	"	16000	-	9.6	1090	1.1
15	700	3.3	95.74	BG70Z-../D09SA4	141	20000	-	18	580	4.0
12.5	840	2.7	113.6	"	"	20000	-	15	700	3.3
11.5	910	2.5	124.0	"	"	20000	-	14	750	3.1
9.6	1090	2.1	147.2	"	"	20000	-	11.5	910	2.5
8.6	1220	1.9	163.8	"	"	20000	-	10.5	1000	2.3
7.3	1430	1.6	194.4	"	"	20000	-	8.7	1200	1.9
6.7	1560	1.45	210.5	"	"	20000	-	8.0	1310	1.75
5.7	1840	1.25	249.8	"	"	20000	-	6.8	1540	1.5
5.5	1800	1.4	255.5	BG70G20-../D09SA4	138	20000	-	6.6	1480	1.7
5.1	1940	1.3	276.7	"	"	20000	-	6.1	1600	1.55
4.3	2300	1.1	328.4	"	"	20000	-	5.2	1880	1.35
3.7	2650	0.94	387.6	"	"	20000	-	4.4	2200	1.15
3.4	2950	0.85	417.8	"	"	20000	-	4.1	2400	1.05
7.5	1400	3.0	186.8	BG80Z-../D09SA4	209	26000	-	9.0	1160	3.6
6.8	1540	2.7	207.4	"	"	26000	-	8.2	1280	3.3
6.2	1410	3.3	227.2	BG80G40-../D09SA4	220	26000	-	7.4	1140	4.0
5.6	1560	2.9	252.3	"	"	26000	-	6.7	1250	3.7
5.0	1790	2.6	282.8	"	"	26000	-	6.0	1440	3.2
4.5	1990	2.3	314.0	"	"	26000	-	5.4	1600	2.9
3.9	2350	1.95	360.0	"	"	26000	-	4.7	1890	2.4
3.6	2500	1.85	399.8	"	"	26000	-	4.3	2050	2.2
3.3	2800	1.65	436.2	"	"	26000	-	3.9	2350	1.95
2.9	3200	1.45	484.3	"	"	26000	-	3.5	2600	1.75
2.5	3800	1.2	572.0	"	"	26000	-	3.0	3100	1.5
2.2	4250	1.1	657.8	"	"	26000	-	2.6	3550	1.3
2.0	4750	0.97	730.3	"	"	26000	-	2.4	3850	1.2
1.8	5300	0.87	817.4	"	"	26000	-	2.1	4450	1.05
3.3	2750	3.3	435.8	BG90G50-../D09SA4	330	65000	-	3.9	2300	4.0
2.8	3250	2.8	504.7	"	"	65000	-	3.4	2600	3.5
2.4	3800	2.4	588.8	"	"	65000	-	2.9	3050	3.0
2.2	4150	2.2	644.7	"	"	65000	-	2.7	3250	2.8
2.0	4600	2.0	714.2	"	"	65000	-	2.4	3700	2.5
1.6	5800	1.6	883.7	"	"	65000	-	2.0	4550	2.0
1.2	8000	1.15	1174	"	"	65000	-	1.5	6300	1.45
1.1	8800	1.05	1301	"	"	65000	-	1.3	7400	1.25
1.7	6100	3.0	845.1	BG100Z-../D09SA4	518	90000	-	2.0	5200	3.6
1.4	6100	3.0	1043	BG100G50-../D09SA4	517	90000	-	1.7	4750	3.9
1.2	7100	2.6	1204	"	"	90000	-	1.4	5800	3.2
1.0	9100	2.0	1444	"	"	90000	-	1.2	7300	2.5
0.85	10700	1.75	1678	"	"	90000	-	1.1	7900	2.3
0.75	12200	1.5	1867	"	"	90000	-	0.9	9800	1.9
0.65	14100	1.3	2154	"	"	90000	-	0.8	11000	1.7
0.55	16700	1.1	2656	"	"	90000	-	0.65	13700	1.35

**P = 1.5 кВт**


50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
560	25.5	2.2	2.52	BG10-../D09LA4	26	560	790	670	21	2.7
410	34.5	1.8	3.42	"	"	630	880	495	28.5	2.2
325	44	1.55	4.36	"	"	650	910	390	36.5	1.85

**P = 1.5 кВт**



50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
265	54	1.4	5.34	BG10-../D09LA4	"	620	910	315	45	1.65
210	68	1.2	6.78	"	"	660	920	250	57	1.4
174	82	1.05	8.07	"	"	660	920	210	68	1.3
151	94	1.05	9.33	"	"	950	1330	181	79	1.25
136	105	0.94	10.34	"	"	1000	1400	163	87	1.15
118	121	0.87	11.92	"	"	1030	1440	141	101	1.05
106	135	0.81	13.21	"	"	1070	1490	128	111	0.99
560	25.5	3.3	2.52	BG20-../D09LA4	28	1660	-	670	21	4.0
425	33.5	2.7	3.33	"	"	1830	-	510	28	3.3
320	44.5	2.3	4.38	"	"	1990	-	385	37	2.8
260	55	2.1	5.49	"	"	2100	-	310	46	2.5
220	65	1.9	6.48	"	"	2250	-	260	55	2.2
175	81	1.7	8.02	"	"	2500	-	210	68	2.0
169	84	1.45	8.29	"	"	2250	-	205	69	1.75
158	90	1.6	8.91	"	"	2600	-	189	75	1.9
146	98	1.25	9.65	"	"	2250	-	175	81	1.5
133	107	1.45	10.54	"	"	2700	-	160	89	1.75
120	119	1.35	11.71	"	"	2800	-	144	99	1.6
106	135	1.25	13.21	"	"	2900	-	128	111	1.5
96	149	1.15	14.67	"	"	3050	-	115	124	1.4
90	159	1.1	15.58	"	"	3100	-	108	132	1.35
81	176	1.05	17.31	"	"	3200	-	98	146	1.25
71	200	0.98	19.95	"	"	3350	-	85	168	1.15
64	220	0.91	22.16	"	"	3500	-	76	188	1.05
61	230	0.87	23.22	"	"	3550	-	73	196	1.0
210	68	3.2	6.75	BG30-../D09LA4	33	1760	-	250	57	3.8
177	80	2.7	7.91	"	"	1760	-	215	66	3.3
163	87	2.8	8.60	"	"	2800	-	196	73	3.4
147	97	2.6	9.55	"	"	3000	-	176	81	3.1
132	108	2.5	10.65	"	"	2950	-	158	90	3.0
119	120	2.3	11.82	"	"	3200	-	143	100	2.7
102	140	2.1	13.77	"	"	3150	-	123	116	2.5
92	155	1.95	15.27	"	"	3450	-	111	129	2.3
83	172	1.75	17.06	"	"	3700	-	99	144	2.1
74	193	1.55	18.93	"	"	4100	-	89	160	1.9
71	200	1.5	19.99	"	"	4200	-	85	168	1.8
64	220	1.35	22.18	"	"	4600	-	76	188	1.6
56	255	1.2	25.45	"	"	4850	-	67	210	1.45
50	285	1.05	28.24	"	"	5100	-	60	235	1.3
47	300	1.0	29.83	"	"	5200	-	57	250	1.2
42.5	335	0.9	33.09	"	"	5400	-	51	280	1.05
40	355	0.85	35.17	"	"	5500	-	48	295	1.0
156	91	3.2	9.00	BG40-../D09LA4	47	2650	-	187	76	3.9
122	117	3.3	11.49	"	"	4600	-	147	97	4.0
109	131	3.1	12.86	"	"	4500	-	131	109	3.8
99	144	2.9	14.28	"	"	4900	-	118	121	3.5
86	166	2.6	16.39	"	"	5300	-	103	139	3.1
77	186	2.3	18.19	"	"	5600	-	93	154	2.8
71	200	2.1	19.84	"	"	5800	-	85	168	2.5
64	220	1.95	22.02	"	"	6000	-	77	186	2.3
60	235	1.8	23.43	"	"	6200	-	72	198	2.1
54	265	1.6	26.01	"	"	6500	-	65	220	1.95
48	295	1.45	29.34	"	"	6800	-	58	245	1.75
43	330	1.3	32.57	"	"	7000	-	52	275	1.55
41	345	1.25	34.20	"	"	7000	-	49.5	285	1.5
37	385	1.1	37.96	"	"	7000	-	44.5	320	1.35
35	405	1.05	40.19	"	"	7000	-	42	340	1.25
31.5	450	0.94	44.62	"	"	7000	-	38	375	1.15
29	490	0.87	48.36	"	"	7000	-	35	405	1.05
64	220	2.9	21.96	BG50-../D09LA4	55	8000	-	77	186	3.4
58	245	2.6	24.34	"	"	8700	-	70	200	3.2
47.5	300	2.1	29.62	"	"	8000	-	57	250	2.5


P = 1.5 кВт



50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
43	330	1.9	32.84	BG50-../D09LA4	"	8700	-	52	275	2.3
37	385	1.65	37.89	"	"	10000	-	44.5	320	1.95
33.5	425	1.5	42.00	"	"	10000	-	40	355	1.75
30	475	1.35	47.02	"	"	10000	-	36	395	1.6
27	530	1.2	52.12	"	"	10000	-	32.5	440	1.45
24	590	1.05	59.42	"	"	10000	-	28.5	500	1.25
21.5	660	0.95	65.86	"	"	10000	-	26	550	1.15
19.5	730	0.86	71.97	BG50Z-../D09LA4	60	10000	-	23.5	600	1.05
18	790	0.8	79.78	"	"	10000	-	21.5	660	0.95
36.5	390	3.1	38.85	BG60-../D09LA4	86	16000	-	43.5	325	3.7
33	430	2.8	43.05	"	"	16000	-	39.5	360	3.3
28	510	2.4	50.31	"	"	16000	-	33.5	425	2.8
25.5	560	2.1	55.76	"	"	16000	-	30.5	465	2.6
23	620	1.95	60.90	"	"	16000	-	28	510	2.4
21	680	1.75	67.49	"	"	16000	-	25	570	2.1
20.5	690	1.75	68.32	BG60Z-../D09LA4	105	16000	-	25	570	2.1
18.5	770	1.55	75.71	"	"	16000	-	22.5	630	1.9
15.5	920	1.3	91.09	"	"	16000	-	18.5	770	1.55
14	1020	1.2	101.0	"	"	16000	-	17	840	1.45
12	1190	1.0	119.2	"	"	16000	-	14.5	980	1.2
11	1300	0.92	132.1	"	"	16000	-	13	1100	1.1
19	750	3.1	73.82	BG70Z-../D09LA4	145	20000	-	23	620	3.7
16	890	2.6	87.61	"	"	20000	-	19.5	730	3.2
15	950	2.4	95.74	"	"	20000	-	18	790	2.9
12.5	1140	2.0	113.6	"	"	20000	-	15	950	2.4
11.5	1240	1.85	124.0	"	"	20000	-	14	1020	2.3
9.6	1490	1.55	147.2	"	"	20000	-	11.5	1240	1.85
8.6	1660	1.4	163.8	"	"	20000	-	10.5	1360	1.7
7.3	1960	1.15	194.4	"	"	20000	-	8.7	1640	1.4
6.7	2100	1.1	210.5	"	"	20000	-	8.0	1790	1.3
5.7	2500	0.92	249.8	"	"	20000	-	6.8	2100	1.1
5.5	2450	1.0	255.5	BG70G20-../D09LA4	142	20000	-	6.6	2050	1.2
5.1	2650	0.94	276.7	"	"	20000	-	6.1	2200	1.15
9.7	1470	2.9	145.4	BG80Z-../D09LA4	213	26000	-	12	1190	3.5
8.7	1640	2.6	161.5	"	"	26000	-	10.5	1360	3.1
7.5	1910	2.2	186.8	"	"	26000	-	9.0	1590	2.6
6.8	2100	2.0	207.4	"	"	26000	-	8.2	1740	2.4
6.2	2000	2.3	227.2	BG80G40-../D09LA4	224	26000	-	7.4	1650	2.8
5.6	2200	2.1	252.3	"	"	26000	-	6.7	1820	2.5
5.0	2550	1.8	282.8	"	"	26000	-	6.0	2050	2.2
4.5	2800	1.65	314.0	"	"	26000	-	5.4	2300	2.0
3.9	3300	1.4	360.0	"	"	26000	-	4.7	2700	1.7
3.6	3600	1.3	399.8	"	"	26000	-	4.3	2950	1.55
3.3	4000	1.15	436.2	"	"	26000	-	3.9	3300	1.4
2.9	4550	1.0	484.3	"	"	26000	-	3.5	3700	1.25
2.5	5300	0.87	572.0	"	"	26000	-	3.0	4350	1.05
4.7	2750	3.3	298.8	BG90G50-../D09LA4	334	65000	-	5.7	2200	4.2
3.9	3150	2.9	360.3	"	"	65000	-	4.7	2550	3.6
3.3	3950	2.3	435.8	"	"	65000	-	3.9	3250	2.8
2.8	4600	2.0	504.7	"	"	65000	-	3.4	3700	2.5
2.4	5400	1.7	588.8	"	"	65000	-	2.9	4350	2.1
2.2	5800	1.6	644.7	"	"	65000	-	2.7	4650	2.0
2.0	6500	1.4	714.2	"	"	65000	-	2.4	5300	1.75
1.6	8200	1.1	883.7	"	"	65000	-	2.0	6400	1.45
1.2	11200	0.82	1174	"	"	65000	-	1.5	8800	1.05
2.4	5900	3.1	591.1	BG100Z-../D09LA4	522	90000	-	2.9	4900	3.8
2.2	6500	2.8	658.1	"	"	90000	-	2.6	5500	3.4
1.9	7500	2.5	759.0	"	"	90000	-	2.3	6200	3.0
1.7	8400	2.2	845.1	"	"	90000	-	2.0	7100	2.6

10


## P = 1.5 кВт



50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
1.5	7900	2.3	976.1	BG100G50-../D09LA4	521	90000	-	1.8	6300	2.9
1.4	8800	2.1	1043	"	"	90000	-	1.7	7000	2.6
1.2	10300	1.8	1204	"	"	90000	-	1.4	8600	2.2
1.0	12900	1.45	1444	"	"	90000	-	1.2	10500	1.75
0.85	15200	1.2	1678	"	"	90000	-	1.1	11400	1.6
0.75	17300	1.05	1867	"	"	90000	-	0.9	14100	1.3


## P = 2.2 кВт

50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
560	37.5	1.5	2.52	BG10-../D09XA4	30	560	790	670	31	1.8
410	51	1.2	3.42	"	"	630	880	495	42	1.5
325	64	1.05	4.36	"	"	650	910	390	53	1.3
265	79	0.95	5.34	"	"	620	910	315	66	1.15
210	100	0.81	6.78	"	"	660	920	250	84	0.96
560	37.5	2.2	2.52	BG20-../D09XA4	32	1660	-	670	31	2.7
425	49	1.9	3.33	"	"	1830	-	510	41	2.2
320	65	1.6	4.38	"	"	1990	-	385	54	1.95
260	80	1.45	5.49	"	"	2100	-	310	67	1.7
220	95	1.3	6.48	"	"	2250	-	260	80	1.55
175	120	1.15	8.02	"	"	2500	-	210	100	1.35
169	124	0.98	8.29	"	"	2250	-	205	102	1.2
158	132	1.1	8.91	"	"	2600	-	189	111	1.3
146	143	0.85	9.65	"	"	2250	-	175	120	1.0
133	157	0.98	10.54	"	"	2700	-	160	131	1.2
120	175	0.9	11.71	"	"	2800	-	144	145	1.1
106	198	0.84	13.21	"	"	2900	-	128	164	1.0
96	215	0.8	14.67	"	"	3050	-	115	182	0.95
530	39.5	3.2	2.67	BG30-../D09XA4	37	1450	-	630	33	3.9
415	50	2.8	3.40	"	"	1580	-	495	42	3.3
335	62	2.8	4.21	"	"	1630	-	400	52	3.3
260	80	2.5	5.44	"	"	1670	-	310	67	3.0
210	100	2.2	6.75	"	"	1760	-	250	84	2.6
177	118	1.85	7.91	"	"	1760	-	215	97	2.2
163	128	1.9	8.60	"	"	2800	-	196	107	2.3
147	142	1.8	9.55	"	"	3000	-	176	119	2.1
132	159	1.65	10.65	"	"	2950	-	158	132	2.0
119	176	1.55	11.82	"	"	3200	-	143	146	1.9
102	205	1.45	13.77	"	"	3150	-	123	170	1.75
92	225	1.35	15.27	"	"	3450	-	111	189	1.6
83	250	1.2	17.06	"	"	3700	-	99	210	1.45
74	280	1.05	18.93	"	"	4100	-	89	235	1.3
71	295	1.0	19.99	"	"	4200	-	85	245	1.2
64	325	0.92	22.18	"	"	4600	-	76	275	1.1
56	375	0.8	25.45	"	"	4850	-	67	310	0.97
225	93	3.2	6.29	BG40-../D09XA4	51	2600	-	270	77	3.8
184	114	2.6	7.62	"	"	2650	-	225	93	3.2
169	124	2.8	8.31	"	"	4100	-	205	102	3.4
156	134	2.2	9.00	"	"	2650	-	187	112	2.6
152	138	2.6	9.23	"	"	4350	-	183	114	3.1
136	154	2.4	10.35	"	"	4350	-	163	128	2.9
122	172	2.3	11.49	"	"	4600	-	147	142	2.7
109	192	2.1	12.86	"	"	4500	-	131	160	2.6
99	210	2.0	14.28	"	"	4900	-	118	178	2.4
86	240	1.75	16.39	"	"	5300	-	103	200	2.1
77	270	1.55	18.19	"	"	5600	-	93	225	1.9
71	295	1.45	19.84	"	"	5800	-	85	245	1.75
64	325	1.3	22.02	"	"	6000	-	77	270	1.55
60	350	1.2	23.43	"	"	6200	-	72	290	1.45
54	385	1.1	26.01	"	"	6500	-	65	320	1.35

**P = 2.2 кВт**


50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
48	435	0.98	29.34	BG40-../D09XA4	"	6800	-	58	360	1.2
43	485	0.88	32.57	"	"	7000	-	52	400	1.05
41	510	0.83	34.20	"	"	7000	-	49.5	420	1.0
117	179	3.2	12.06	BG50-../D09XA4	59	5700	-	140	150	3.8
105	200	3.0	13.36	"	"	6100	-	126	166	3.6
85	245	2.6	16.53	"	"	6500	-	102	205	3.1
77	270	2.3	18.33	"	"	7200	-	92	225	2.8
64	325	1.95	21.96	"	"	8000	-	77	270	2.3
58	360	1.75	24.34	"	"	8700	-	70	300	2.1
47.5	440	1.45	29.62	"	"	8000	-	57	365	1.75
43	485	1.3	32.84	"	"	8700	-	52	400	1.6
37	560	1.15	37.89	"	"	10000	-	44.5	470	1.35
33.5	620	1.0	42.00	"	"	10000	-	40	520	1.2
30	700	0.9	47.02	"	"	10000	-	36	580	1.1
27	770	0.82	52.12	"	"	10000	-	32.5	640	0.98
57	365	3.3	24.82	BG60-../D09XA4	90	13800	-	68	305	3.9
48	435	2.8	29.31	"	"	14800	-	58	360	3.3
43.5	480	2.5	32.48	"	"	15400	-	52	400	3.0
36.5	570	2.1	38.85	"	"	16000	-	43.5	480	2.5
33	630	1.9	43.05	"	"	16000	-	39.5	530	2.3
28	750	1.6	50.31	"	"	16000	-	33.5	620	1.95
25.5	820	1.45	55.76	"	"	16000	-	30.5	680	1.75
23	910	1.3	60.90	"	"	16000	-	28	750	1.6
21	1000	1.2	67.49	"	"	16000	-	25	840	1.45
20.5	1020	1.2	68.32	BG60Z-../D09XA4	109	16000	-	25	840	1.45
18.5	1130	1.05	75.71	"	"	16000	-	22.5	930	1.3
15.5	1350	0.89	91.09	"	"	16000	-	18.5	1130	1.05
14	1500	0.8	101.0	"	"	16000	-	17	1230	0.98
28	750	3.1	50.40	BG70-../D09XA4	128	20000	-	33.5	620	3.7
23.5	890	2.6	59.82	"	"	20000	-	28.5	730	3.2
22	950	2.4	64.85	BG70Z-../D09XA4	149	20000	-	26	800	2.9
19	1100	2.1	73.82	"	"	20000	-	23	910	2.5
16	1310	1.75	87.61	"	"	20000	-	19.5	1070	2.1
15	1400	1.65	95.74	"	"	20000	-	18	1160	2.0
12.5	1680	1.35	113.6	"	"	20000	-	15	1400	1.65
11.5	1820	1.25	124.0	"	"	20000	-	14	1500	1.55
9.6	2150	1.05	147.2	"	"	20000	-	11.5	1820	1.25
8.6	2400	0.96	163.8	"	"	20000	-	10.5	2000	1.15
7.3	2850	0.81	194.4	"	"	20000	-	8.7	2400	0.96
15	1400	3.0	93.89	BG80Z-../D09XA4	217	26000	-	18	1160	3.6
12.5	1680	2.5	112.4	"	"	26000	-	15	1400	3.0
11.5	1820	2.3	124.8	"	"	26000	-	13.5	1550	2.7
9.7	2150	1.95	145.4	"	"	26000	-	12	1750	2.4
8.7	2400	1.75	161.5	"	"	26000	-	10.5	2000	2.1
7.5	2800	1.5	186.8	"	"	26000	-	9.0	2300	1.85
6.8	3050	1.4	207.4	"	"	26000	-	8.2	2550	1.65
6.2	3100	1.5	227.2	BG80G40-../D09XA4	228	26000	-	7.4	2550	1.8
5.6	3400	1.35	252.3	"	"	26000	-	6.7	2800	1.65
5.0	3850	1.2	282.8	"	"	26000	-	6.0	3150	1.45
4.5	4300	1.05	314.0	"	"	26000	-	5.4	3550	1.3
3.9	5000	0.92	360.0	"	"	26000	-	4.7	4100	1.1
3.6	5400	0.85	399.8	"	"	26000	-	4.3	4500	1.0
7.9	2650	3.2	178.5	BG90Z-../D09XA4	327	65000	-	9.5	2200	3.8
6.8	3050	2.8	208.3	"	"	65000	-	8.1	2550	3.3
6.2	3350	2.5	228.1	"	"	65000	-	7.4	2800	3.0
5.4	3450	2.7	262.5	BG90G50-../D09XA4	338	65000	-	6.4	2850	3.2
4.7	4150	2.2	298.8	"	"	65000	-	5.7	3400	2.7
3.9	4900	1.9	360.3	"	"	65000	-	4.7	3950	2.3
3.3	5900	1.55	435.8	"	"	65000	-	3.9	4950	1.85
2.8	7000	1.3	504.7	"	"	65000	-	3.4	5600	1.65
2.4	8100	1.15	588.8	"	"	65000	-	2.9	6600	1.4

## P = 2.2 кВт




50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
2.2	8900	1.05	644.7	BG90G50-../D09XA4	"	65000	-	2.7	7100	1.3
2.0	9800	0.94	714.2	"	"	65000	-	2.4	8100	1.15
3.7	5600	3.3	382.6	BG100Z-../D09XA4	526	90000	-	4.4	4750	3.9
3.1	6700	2.8	456.7	"	"	90000	-	3.7	5600	3.3
2.8	7500	2.5	508.5	"	"	90000	-	3.4	6100	3.0
2.4	8700	2.1	591.1	"	"	90000	-	2.9	7200	2.6
2.2	9500	1.95	658.1	"	"	90000	-	2.6	8000	2.3
1.9	11000	1.7	759.0	"	"	90000	-	2.3	9100	2.0
1.7	12300	1.5	845.1	"	"	90000	-	2.0	10500	1.75
1.5	12400	1.5	976.1	BG100G50-../D09XA4	525	90000	-	1.8	10000	1.85
1.4	13600	1.35	1043	"	"	90000	-	1.7	10900	1.7
1.2	15800	1.15	1204	"	"	90000	-	1.4	13300	1.4
1.0	19600	0.94	1444	"	"	90000	-	1.2	16100	1.15

## P = 3 кВт

50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
540	53	2.4	2.67	BG30-../D11SA4	40	1450	-	650	44	2.9
420	68	2.0	3.40	"	"	1580	-	510	56	2.5
340	84	2.0	4.21	"	"	1630	-	410	69	2.5
265	108	1.85	5.44	"	"	1670	-	315	90	2.2
215	133	1.65	6.75	"	"	1760	-	255	112	1.95
180	159	1.35	7.91	"	"	1760	-	220	130	1.65
166	172	1.45	8.60	"	"	2800	-	199	143	1.7
149	192	1.3	9.55	"	"	3000	-	180	159	1.6
134	210	1.25	10.65	"	"	2950	-	161	177	1.5
121	235	1.15	11.82	"	"	3200	-	145	197	1.4
104	275	1.05	13.77	"	"	3150	-	125	225	1.3
93	305	0.98	15.27	"	"	3450	-	112	255	1.2
84	340	0.88	17.06	"	"	3700	-	101	280	1.05
76	375	0.8	18.93	"	"	4100	-	91	310	0.97
360	79	3.1	3.97	BG40-../D11SA4	59	2400	-	435	65	3.8
290	98	2.7	4.94	"	"	2450	-	350	81	3.3
230	124	2.4	6.29	"	"	2600	-	275	104	2.8
187	153	1.95	7.62	"	"	2650	-	225	127	2.3
171	167	2.1	8.31	"	"	4100	-	210	136	2.5
158	181	1.65	9.00	"	"	2650	-	190	150	1.95
154	186	1.9	9.23	"	"	4350	-	186	154	2.3
138	205	1.85	10.35	"	"	4350	-	166	172	2.2
124	230	1.7	11.49	"	"	4600	-	149	192	2.0
111	255	1.6	12.86	"	"	4500	-	133	215	1.9
100	285	1.5	14.28	"	"	4900	-	120	235	1.8
87	325	1.3	16.39	"	"	5300	-	105	270	1.55
79	360	1.2	18.19	"	"	5600	-	95	300	1.4
72	395	1.1	19.84	"	"	5800	-	87	325	1.3
65	440	0.97	22.02	"	"	6000	-	78	365	1.15
61	465	0.91	23.43	"	"	6200	-	73	390	1.1
55	520	0.82	26.01	"	"	6500	-	66	430	0.99
164	174	2.9	8.70	BG50-../D11SA4	69	5300	-	197	145	3.5
148	193	2.7	9.65	"	"	5600	-	178	160	3.3
118	240	2.4	12.06	"	"	5700	-	142	200	2.9
107	265	2.2	13.36	"	"	6100	-	128	220	2.7
86	330	1.9	16.53	"	"	6500	-	104	275	2.3
78	365	1.75	18.33	"	"	7200	-	94	300	2.1
65	440	1.45	21.96	"	"	8000	-	78	365	1.75
59	485	1.3	24.34	"	"	8700	-	71	400	1.6
48	590	1.05	29.62	"	"	8000	-	58	490	1.3
43.5	650	0.97	32.84	"	"	8700	-	53	540	1.15
37.5	760	0.83	37.89	"	"	10000	-	45.5	620	1.0
85	335	3.3	16.80	BG60-../D11SA4	101	12000	-	102	280	4.0
77	370	3.1	18.62	"	"	12400	-	92	310	3.7



P = 3 кВт



50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
64	445	2.7	22.40	BG60-../D11SA4	"	13300	-	77	370	3.2
58	490	2.4	24.82	"	"	13800	-	69	415	2.9
48.5	590	2.0	29.31	"	"	14800	-	59	485	2.5
44	650	1.85	32.48	"	"	15400	-	53	540	2.2
37	770	1.55	38.85	"	"	16000	-	44.5	640	1.9
33	860	1.4	43.05	"	"	16000	-	40	710	1.7
28.5	1000	1.2	50.31	"	"	16000	-	34	840	1.45
25.5	1120	1.05	55.76	"	"	16000	-	31	920	1.3
23.5	1210	0.99	60.90	"	"	16000	-	28.5	1000	1.2
21.5	1330	0.9	67.49	"	"	16000	-	25.5	1120	1.05
21	1360	0.88	68.32	BG60Z-../D11SA4	117	16000	-	25.5	1120	1.05
19	1500	0.8	75.71	"	"	16000	-	23	1240	0.97
40.5	700	3.3	35.24	BG70-../D11SA4	132	18300	-	49	580	4.0
36.5	780	2.9	39.22	"	"	19100	-	44	650	3.5
31	920	2.5	46.54	"	"	20000	-	37	770	3.0
28.5	1000	2.3	50.40	"	"	20000	-	34	840	2.7
24	1190	1.95	59.82	"	"	20000	-	29	980	2.3
22	1300	1.75	64.85	BG70Z-../D11SA4	158	20000	-	26.5	1080	2.1
19.5	1460	1.6	73.82	"	"	20000	-	23.5	1210	1.9
16.5	1730	1.35	87.61	"	"	20000	-	20	1430	1.6
15	1910	1.2	95.74	"	"	20000	-	18	1590	1.45
12.5	2250	1.0	113.6	"	"	20000	-	15.5	1840	1.25
11.5	2450	0.94	124.0	"	"	20000	-	14	2000	1.15
22.5	1270	3.3	63.56	BG80-../D11SA4	186	26000	-	27	1060	4.0
21.5	1330	3.2	66.40	BG80Z-../D11SA4	228	26000	-	26	1100	3.8
19.5	1460	2.9	73.73	"	"	26000	-	23.5	1210	3.5
17	1680	2.5	84.55	"	"	26000	-	20.5	1390	3.0
15.5	1840	2.3	93.89	"	"	26000	-	18.5	1540	2.7
13	2200	1.9	112.4	"	"	26000	-	15.5	1840	2.3
11.5	2450	1.7	124.8	"	"	26000	-	14	2000	2.1
9.8	2900	1.45	145.4	"	"	26000	-	12	2350	1.8
8.8	3250	1.3	161.5	"	"	26000	-	11	2600	1.6
7.7	3700	1.15	186.8	"	"	26000	-	9.2	3100	1.35
6.9	4150	1.0	207.4	"	"	26000	-	8.3	3450	1.2
6.3	4250	1.1	227.2	BG80G40-../D11SA4	236	26000	-	7.6	3450	1.35
5.7	4700	0.98	252.3	"	"	26000	-	6.8	3900	1.2
5.1	5300	0.87	282.8	"	"	26000	-	6.1	4350	1.05
10.5	2700	3.1	139.2	BG90Z-../D11SA4	330	65000	-	12.5	2250	3.7
8.8	3250	2.6	163.0	"	"	65000	-	10.5	2700	3.1
8.0	3550	2.4	178.5	"	"	65000	-	9.6	2950	2.8
6.9	4150	2.0	208.3	"	"	65000	-	8.3	3450	2.4
6.3	4500	1.85	228.1	"	"	65000	-	7.5	3800	2.2
5.5	4750	1.95	262.5	BG90G50-../D11SA4	347	65000	-	6.6	3900	2.4
4.8	5600	1.65	298.8	"	"	65000	-	5.8	4650	2.0
4.0	6600	1.4	360.3	"	"	65000	-	4.8	5400	1.7
3.3	8200	1.1	435.8	"	"	65000	-	4.0	6700	1.35
2.9	9300	0.99	504.7	"	"	65000	-	3.4	7900	1.15
2.5	10800	0.85	588.8	"	"	65000	-	3.0	8900	1.05
5.5	5200	3.2	259.0	BG100-../D11SA4	447	90000	-	6.7	4250	4.0
4.8	5900	3.1	300.4	BG100Z-../D11SA4	537	90000	-	5.7	5000	3.7
4.2	6800	2.7	343.6	"	"	90000	-	5.0	5700	3.2
3.8	7500	2.5	382.6	"	"	90000	-	4.5	6300	2.9
3.2	8900	2.1	456.7	"	"	90000	-	3.8	7500	2.5
2.8	10200	1.8	508.5	"	"	90000	-	3.4	8400	2.2
2.5	11400	1.6	591.1	"	"	90000	-	2.9	9800	1.9
2.2	13000	1.4	658.1	"	"	90000	-	2.6	11000	1.7
1.9	15000	1.25	759.0	"	"	90000	-	2.3	12400	1.5
1.7	16800	1.1	845.1	"	"	90000	-	2.1	13600	1.35
1.5	17500	1.05	976.1	BG100G50-../D11SA4	534	90000	-	1.8	14300	1.3
1.4	19000	0.97	1043	"	"	90000	-	1.7	15400	1.2
1.2	22200	0.83	1204	"	"	90000	-	1.5	17400	1.05