



P = 1.5 кВт




50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
250	57	2.4	5.60	BF10-../D09LA4	36	1980	-	300	47.5	2.9
185	77	2.0	7.58	"	"	2200	-	225	63	2.4
145	98	1.8	9.69	"	"	2350	-	174	82	2.2
119	120	1.55	11.84	"	"	2500	-	142	100	1.85
94	152	1.2	15.04	"	"	2800	-	112	127	1.45
77	186	1.3	18.23	"	"	2900	-	93	154	1.55
70	200	1.2	20.05	"	"	3000	-	84	170	1.4
61	230	1.05	23.28	"	"	3200	-	73	196	1.2
55	260	0.92	25.60	"	"	3350	-	66	215	1.1
49.5	285	0.84	28.47	"	"	3450	-	60	235	1.0
235	60	3.3	6.04	BF20-../D09LA4	42	2550	-	280	51	3.9
175	81	2.7	8.00	"	"	2850	-	210	68	3.2
134	106	2.4	10.51	"	"	3100	-	160	89	2.9
107	133	2.1	13.18	"	"	3300	-	128	111	2.6
91	157	1.95	15.54	"	"	3450	-	109	131	2.4
84	170	2.1	16.77	"	"	3500	-	101	141	2.6
76	188	1.95	18.45	"	"	3600	-	92	155	2.4
64	220	1.8	22.04	"	"	3800	-	77	186	2.1
58	245	1.65	24.25	"	"	3950	-	70	200	2.0
51	280	1.5	27.62	"	"	4150	-	61	230	1.85
46.5	305	1.4	30.40	"	"	4400	-	56	255	1.65
43	330	1.25	32.58	"	"	4450	-	52	275	1.55
39.5	360	1.15	35.85	"	"	4650	-	47	300	1.4
34	420	1.0	41.72	"	"	4950	-	40.5	350	1.2
31	460	0.91	45.90	"	"	5100	-	37	385	1.1
29	490	0.86	48.56	"	"	5200	-	35	405	1.05
141	101	3.2	9.99	BF30-../D09LA4	53	2850	-	169	84	3.8
109	131	2.8	12.91	"	"	3050	-	131	109	3.4
88	162	2.5	16.00	"	"	3250	-	105	136	3.0
80	179	2.7	17.65	"	"	3300	-	96	149	3.2
73	196	2.6	19.41	"	"	3400	-	87	164	3.1
65	220	2.4	21.85	"	"	3500	-	77	186	2.8
59	240	2.3	24.03	"	"	3600	-	70	200	2.8
50	285	2.0	28.23	"	"	3800	-	60	235	2.4
45.5	310	1.85	31.05	"	"	4000	-	55	260	2.2
40	355	1.6	35.00	"	"	4200	-	48	295	1.95
36.5	390	1.45	38.49	"	"	4400	-	44	325	1.75
34.5	415	1.4	41.01	"	"	4500	-	41	345	1.65
31.5	450	1.3	45.10	"	"	4700	-	37.5	380	1.5
27	530	1.1	52.20	"	"	5000	-	32.5	440	1.3
24.5	580	0.99	57.41	"	"	5200	-	29.5	485	1.2
23	620	0.93	61.17	"	"	5300	-	27.5	520	1.1
21	680	0.85	67.28	"	"	5500	-	25	570	1.0
65	220	3.2	21.60	BF40-../D09LA4	62	5200	-	78	183	3.8
59	240	3.1	23.77	"	"	5400	-	71	200	3.7
53	270	2.9	26.86	"	"	5600	-	63	225	3.4
47.5	300	2.7	29.55	"	"	5800	-	57	250	3.2
41	345	2.5	34.21	"	"	6000	-	49.5	285	3.0
37.5	380	2.4	37.64	"	"	6200	-	45	315	2.8
34	420	2.1	41.42	"	"	6500	-	41	345	2.6
31	460	1.95	45.56	"	"	6800	-	37	385	2.3
29	490	1.85	48.92	"	"	7000	-	34.5	415	2.2
26.5	540	1.65	53.82	"	"	7200	-	31.5	450	2.0
23	620	1.45	61.25	"	"	7600	-	27.5	520	1.75
21	680	1.3	67.38	"	"	8000	-	25	570	1.6
20	710	1.25	71.40	"	"	8100	-	24	590	1.55
18	790	1.15	78.55	"	"	8500	-	21.5	660	1.35
17	840	1.05	83.91	"	"	8700	-	20.5	690	1.3
15.5	920	0.98	92.31	"	"	9100	-	18.5	770	1.15
14	1020	0.88	101.0	"	"	9400	-	17	840	1.05

P = 1.5 кВт




50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
13	1100	0.82	111.1	BF40-../D09LA4	"	9800	-	15.5	920	0.98
33.5	425	3.1	42.15	BF50-../D09LA4	90	8500	-	40	355	3.7
30	475	2.7	47.14	"	"	8900	-	36	395	3.3
25	570	2.3	56.86	"	"	9300	-	30	475	2.7
22.5	630	2.1	63.59	"	"	9800	-	26.5	540	2.4
19.5	730	1.8	72.72	"	"	10700	-	23.5	600	2.2
17.5	810	1.6	81.33	"	"	11300	-	21	680	1.9
16	890	1.45	90.24	"	"	11800	-	19	750	1.75
14	1020	1.25	100.9	"	"	12300	-	17	840	1.55
12.5	1140	1.15	114.0	"	"	12900	-	15	950	1.35
11	1300	1.0	127.5	"	"	13600	-	13.5	1060	1.25
10.5	1360	0.96	138.1	BF50Z-../D09LA4	95	13600	-	12.5	1140	1.15
9.1	1570	0.83	154.5	"	"	13600	-	11	1300	1.0
19.5	730	3.2	72.15	BF60-../D09LA4	120	12000	34000	23.5	600	3.8
17.5	810	2.8	80.05	"	"	12600	35600	21	680	3.4
15	950	2.4	93.44	"	"	13500	38200	18	790	2.9
14	1020	2.3	103.7	"	"	14100	39900	16.5	860	2.7
12.5	1140	2.0	113.1	"	"	14600	41300	15	950	2.4
11.5	1240	1.85	125.5	"	"	15300	43300	13.5	1060	2.2
10	1430	1.6	140.8	BF60Z-../D09LA4	139	15300	43300	12	1190	1.95
8.3	1720	1.35	169.2	"	"	15300	43300	10	1430	1.6
7.5	1910	1.2	187.7	"	"	15300	43300	9.0	1590	1.45
6.4	2200	1.05	221.4	"	"	15300	43300	7.6	1880	1.2
5.8	2450	0.94	245.6	"	"	15300	43300	6.9	2050	1.1
9.1	1570	3.3	154.0	BF70Z-../D09LA4	227	16100	47700	11	1300	4.0
7.8	1830	2.8	179.7	"	"	16100	47700	9.4	1520	3.4
7.1	2000	2.6	199.7	"	"	16100	47700	8.5	1680	3.1
6.1	2300	2.3	233.0	"	"	16100	47700	7.3	1960	2.7
5.5	2600	2.0	258.7	"	"	16100	47700	6.5	2200	2.4
4.7	3000	1.75	301.8	"	"	16100	47700	5.6	2550	2.0
4.1	3450	1.5	341.7	"	"	16100	47700	5.0	2850	1.8
3.6	3950	1.3	398.7	"	"	16100	47700	4.3	3300	1.6
3.2	4450	1.15	439.2	"	"	16100	47700	3.9	3650	1.4
2.8	5100	1.0	512.4	"	"	16100	47700	3.3	4300	1.2
2.7	5000	1.15	524.1	BF70G20-../D09LA4	225	16100	47700	3.3	4100	1.4
2.5	5400	1.05	577.5	"	"	16100	47700	3.0	4500	1.25
2.1	6500	0.88	673.6	"	"	16100	47700	2.5	5400	1.05
4.1	3450	3.0	347.3	BF80Z-../D09LA4	344	39600	75000	4.9	2900	3.6
3.6	3950	2.7	394.2	"	"	39600	75000	4.3	3300	3.2
3.2	4450	2.4	450.4	"	"	39600	75000	3.8	3750	2.8
2.8	5100	2.1	511.2	"	"	39600	75000	3.3	4300	2.4
2.4	5900	1.8	583.4	"	"	39600	75000	2.9	4900	2.1
2.2	6500	1.6	662.1	"	"	39600	75000	2.6	5500	1.9
1.9	7500	1.4	770.6	"	"	39600	75000	2.2	6500	1.6
1.7	8400	1.25	874.6	"	"	39600	75000	2.0	7100	1.5
1.5	9500	1.1	990.4	"	"	39600	75000	1.7	8400	1.25
1.3	11000	0.95	1124	"	"	39600	75000	1.5	9500	1.1
1.1	11500	0.91	1329	BF80G40-../D09LA4	349	39600	75000	1.3	9500	1.1
2.4	5900	3.1	591.1	BF90Z-../D09LA4	608	42800	120000	2.9	4900	3.8
2.2	6500	2.8	658.1	"	"	42800	120000	2.6	5500	3.4
1.9	7500	2.5	759.0	"	"	42800	120000	2.3	6200	3.0
1.7	8400	2.2	845.1	"	"	42800	120000	2.0	7100	2.6
1.5	7900	2.3	976.1	BF90G50-../D09LA4	620	42800	120000	1.8	6300	2.9
1.4	8800	2.1	1043	"	"	42800	120000	1.7	7000	2.6
1.2	10300	1.8	1204	"	"	42800	120000	1.4	8600	2.2
1.0	12900	1.45	1444	"	"	42800	120000	1.2	10500	1.75
0.85	15200	1.2	1678	"	"	42800	120000	1.1	11400	1.6
0.75	17300	1.05	1867	"	"	42800	120000	0.9	14100	1.3

P = 2.2 кВт




50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
250	84	1.65	5.60	BF10-../D09XA4	40	1980	-	300	70	1.95
185	113	1.35	7.58	"	"	2200	-	225	93	1.65
145	144	1.25	9.69	"	"	2350	-	174	120	1.5
119	176	1.05	11.84	"	"	2500	-	142	147	1.25
94	220	0.83	15.04	"	"	2800	-	112	187	0.98
77	270	0.89	18.23	"	"	2900	-	93	225	1.05
70	300	0.8	20.05	"	"	3000	-	84	250	0.96
235	89	2.2	6.04	BF20-../D09XA4	46	2550	-	280	75	2.7
175	120	1.85	8.00	"	"	2850	-	210	100	2.2
134	156	1.65	10.51	"	"	3100	-	160	131	1.95
107	196	1.45	13.18	"	"	3300	-	128	164	1.75
91	230	1.35	15.54	"	"	3450	-	109	192	1.6
84	250	1.45	16.77	"	"	3500	-	101	205	1.75
76	275	1.35	18.45	"	"	3600	-	92	225	1.65
64	325	1.2	22.04	"	"	3800	-	77	270	1.45
58	360	1.1	24.25	"	"	3950	-	70	300	1.35
51	410	1.0	27.62	"	"	4150	-	61	340	1.25
46.5	450	0.93	30.40	"	"	4400	-	56	375	1.1
43	485	0.87	32.58	"	"	4450	-	52	400	1.05
225	93	2.8	6.34	BF30-../D09XA4	57	2400	-	265	79	3.3
174	120	2.4	8.07	"	"	2650	-	210	100	2.9
141	149	2.1	9.99	"	"	2850	-	169	124	2.6
109	192	1.9	12.91	"	"	3050	-	131	160	2.3
88	235	1.75	16.00	"	"	3250	-	105	200	2.0
80	260	1.85	17.65	"	"	3300	-	96	215	2.2
73	285	1.75	19.41	"	"	3400	-	87	240	2.1
65	320	1.65	21.85	"	"	3500	-	77	270	1.95
59	355	1.55	24.03	"	"	3600	-	70	300	1.85
50	420	1.35	28.23	"	"	3800	-	60	350	1.65
45.5	460	1.25	31.05	"	"	4000	-	55	380	1.5
40	520	1.1	35.00	"	"	4200	-	48	435	1.3
36.5	570	1.0	38.49	"	"	4400	-	44	475	1.2
34.5	600	0.96	41.01	"	"	4500	-	41	510	1.15
31.5	660	0.87	45.10	"	"	4700	-	37.5	560	1.05
184	114	3.2	7.62	BF40-../D09XA4	66	3900	-	225	93	4.0
148	141	2.9	9.48	"	"	4150	-	178	118	3.5
119	176	2.6	11.79	"	"	4450	-	143	146	3.2
94	220	2.4	15.02	"	"	4800	-	112	187	2.8
81	255	2.5	17.35	"	"	4950	-	97	215	3.0
74	280	2.4	19.09	"	"	5100	-	89	235	2.8
65	320	2.2	21.60	"	"	5200	-	78	265	2.7
59	355	2.1	23.77	"	"	5400	-	71	295	2.5
53	395	1.95	26.86	"	"	5600	-	63	330	2.3
47.5	440	1.85	29.55	"	"	5800	-	57	365	2.2
41	510	1.7	34.21	"	"	6000	-	49.5	420	2.0
37.5	560	1.6	37.64	"	"	6200	-	45	465	1.9
34	610	1.5	41.42	"	"	6500	-	41	510	1.75
31	670	1.35	45.56	"	"	6800	-	37	560	1.6
29	720	1.25	48.92	"	"	7000	-	34.5	600	1.5
26.5	790	1.15	53.82	"	"	7200	-	31.5	660	1.35
23	910	0.99	61.25	"	"	7600	-	27.5	760	1.2
21	1000	0.9	67.38	"	"	8000	-	25	840	1.05
20	1050	0.86	71.40	"	"	8100	-	24	870	1.05
61	340	3.3	23.14	BF50-../D09XA4	94	6800	-	73	285	3.9
55	380	3.1	25.88	"	"	7100	-	65	320	3.6
44.5	470	2.7	31.73	"	"	7500	-	53	395	3.2
39.5	530	2.5	35.49	"	"	7800	-	47.5	440	3.0
33.5	620	2.1	42.15	"	"	8500	-	40	520	2.5
30	700	1.85	47.14	"	"	8900	-	36	580	2.2


P = 2.2 кВт


50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
25	840	1.55	56.86	BF50-../D09XA4	"	9300	-	30	700	1.85
22.5	930	1.4	63.59	"	"	9800	-	26.5	790	1.65
19.5	1070	1.2	72.72	"	"	10700	-	23.5	890	1.45
17.5	1200	1.1	81.33	"	"	11300	-	21	1000	1.3
16	1310	0.99	90.24	"	"	11800	-	19	1100	1.2
14	1500	0.87	100.9	"	"	12300	-	17	1230	1.05
30.5	680	3.3	46.16	BF60-../D09XA4	124	9900	28000	36.5	570	3.9
26	800	2.9	54.44	"	"	10500	29700	31	670	3.4
23.5	890	2.6	60.40	"	"	11100	31400	28	750	3.1
19.5	1070	2.1	72.15	"	"	12000	34000	23.5	890	2.6
17.5	1200	1.9	80.05	"	"	12600	35600	21	1000	2.3
15	1400	1.65	93.44	"	"	13500	38200	18	1160	2.0
14	1500	1.55	103.7	"	"	14100	39900	16.5	1270	1.8
12.5	1680	1.35	113.1	"	"	14600	41300	15	1400	1.65
11.5	1820	1.25	125.5	"	"	15300	43300	13.5	1550	1.5
10	2100	1.1	140.8	BF60Z-../D09XA4	143	15300	43300	12	1750	1.3
8.3	2500	0.92	169.2	"	"	15300	43300	10	2100	1.1
7.5	2800	0.82	187.7	"	"	15300	43300	9.0	2300	1.0
11.5	1820	2.9	122.7	BF70-../D09XA4	210	16100	47700	14	1500	3.5
11	1910	2.7	133.0	BF70Z-../D09XA4	231	16100	47700	13	1610	3.2
9.1	2300	2.3	154.0	"	"	16100	47700	11	1910	2.7
7.8	2650	1.95	179.7	"	"	16100	47700	9.4	2200	2.4
7.1	2950	1.75	199.7	"	"	16100	47700	8.5	2450	2.1
6.1	3400	1.55	233.0	"	"	16100	47700	7.3	2850	1.8
5.5	3800	1.35	258.7	"	"	16100	47700	6.5	3200	1.65
4.7	4450	1.15	301.8	"	"	16100	47700	5.6	3750	1.4
4.1	5100	1.0	341.7	"	"	16100	47700	5.0	4200	1.25
3.6	5800	0.9	398.7	"	"	16100	47700	4.3	4850	1.05
3.2	6500	0.8	439.2	"	"	16100	47700	3.9	5300	0.98
6.7	3100	3.1	209.4	BF80-../D09XA4	307	34300	75000	8.1	2550	3.7
6.0	3500	2.7	237.1	"	"	36900	75000	7.1	2950	3.2
5.3	3950	2.4	269.1	"	"	39600	75000	6.3	3300	2.9
4.8	4350	2.4	291.7	BF80Z-../D09XA4	348	39600	75000	5.8	3600	2.9
4.1	5100	2.1	347.3	"	"	39600	75000	4.9	4250	2.5
3.6	5800	1.8	394.2	"	"	39600	75000	4.3	4850	2.2
3.2	6500	1.6	450.4	"	"	39600	75000	3.8	5500	1.9
2.8	7500	1.4	511.2	"	"	39600	75000	3.3	6300	1.65
2.4	8700	1.2	583.4	"	"	39600	75000	2.9	7200	1.45
2.2	9500	1.1	662.1	"	"	39600	75000	2.6	8000	1.3
1.9	11000	0.95	770.6	"	"	39600	75000	2.2	9500	1.1
1.7	12300	0.85	874.6	"	"	39600	75000	2.0	10500	1.0
3.7	5600	3.3	382.6	BF90Z-../D09XA4	612	42800	120000	4.4	4750	3.9
3.1	6700	2.8	456.7	"	"	42800	120000	3.7	5600	3.3
2.8	7500	2.5	508.5	"	"	42800	120000	3.4	6100	3.0
2.4	8700	2.1	591.1	"	"	42800	120000	2.9	7200	2.6
2.2	9500	1.95	658.1	"	"	42800	120000	2.6	8000	2.3
1.9	11000	1.7	759.0	"	"	42800	120000	2.3	9100	2.0
1.7	12300	1.5	845.1	"	"	42800	120000	2.0	10500	1.75
1.5	12400	1.5	976.1	BF90G50-../D09XA4	624	42800	120000	1.8	10000	1.85
1.4	13600	1.35	1043	"	"	42800	120000	1.7	10900	1.7
1.2	15800	1.15	1204	"	"	42800	120000	1.4	13300	1.4
1.0	19600	0.94	1444	"	"	42800	120000	1.2	16100	1.15

P = 3 кВт



50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
225	127	2.1	6.34	BF30-../D11SA4	60	2400	-	270	106	2.5
176	162	1.75	8.07	"	"	2650	-	215	133	2.2
143	200	1.6	9.99	"	"	2850	-	172	166	1.95
110	260	1.4	12.91	"	"	3050	-	133	215	1.7
89	320	1.3	16.00	"	"	3250	-	107	265	1.55
81	350	1.35	17.65	"	"	3300	-	97	295	1.6
74	385	1.3	19.41	"	"	3400	-	89	320	1.55
65	440	1.2	21.85	"	"	3500	-	79	360	1.45
60	475	1.15	24.03	"	"	3600	-	72	395	1.4
51	560	1.05	28.23	"	"	3800	-	61	465	1.25
46	620	0.93	31.05	"	"	4000	-	56	510	1.15
41	690	0.83	35.00	"	"	4200	-	49	580	0.99
245	116	2.9	5.87	BF40-../D11SA4	74	3550	-	295	97	3.5
187	153	2.4	7.62	"	"	3900	-	225	127	2.9
150	191	2.2	9.48	"	"	4150	-	181	158	2.6
121	235	2.0	11.79	"	"	4450	-	146	196	2.4
95	300	1.75	15.02	"	"	4800	-	114	250	2.1
82	345	1.85	17.35	"	"	4950	-	99	285	2.2
75	380	1.75	19.09	"	"	5100	-	90	315	2.1
66	430	1.65	21.60	"	"	5200	-	80	355	2.0
60	475	1.55	23.77	"	"	5400	-	72	395	1.85
53	540	1.45	26.86	"	"	5600	-	64	445	1.75
48.5	590	1.35	29.55	"	"	5800	-	58	490	1.65
42	680	1.25	34.21	"	"	6000	-	50	570	1.5
38	750	1.2	37.64	"	"	6200	-	45.5	620	1.45
34.5	830	1.1	41.42	"	"	6500	-	41.5	690	1.3
31.5	900	1.0	45.56	"	"	6800	-	38	750	1.2
29.5	970	0.93	48.92	"	"	7000	-	35	810	1.1
26.5	1080	0.83	53.82	"	"	7200	-	32	890	1.0
133	215	3.1	10.68	BF50-../D11SA4	104	5600	-	161	177	3.8
97	295	2.7	14.65	"	"	6100	-	117	240	3.3
86	330	2.9	16.70	"	"	6200	-	103	275	3.5
77	370	2.7	18.68	"	"	6400	-	92	310	3.2
62	460	2.4	23.14	"	"	6800	-	74	385	2.9
55	520	2.2	25.88	"	"	7100	-	67	425	2.7
45	630	2.0	31.73	"	"	7500	-	54	530	2.4
40.5	700	1.85	35.49	"	"	7800	-	48.5	590	2.2
34	840	1.55	42.15	"	"	8500	-	41	690	1.9
30.5	930	1.4	47.14	"	"	8900	-	36.5	780	1.65
25	1140	1.15	56.86	"	"	9300	-	30.5	930	1.4
22.5	1270	1.0	63.59	"	"	9800	-	27	1060	1.25
20	1430	0.91	72.72	"	"	10700	-	24	1190	1.1
17.5	1630	0.8	81.33	"	"	11300	-	21.5	1330	0.98
46	620	3.1	31.20	BF60-../D11SA4	135	8800	24900	55	520	3.7
41.5	690	2.9	34.62	"	"	9100	25700	49.5	570	3.5
34.5	830	2.6	41.60	"	"	9600	27100	41.5	690	3.1
31	920	2.4	46.16	"	"	9900	28000	37.5	760	2.9
26.5	1080	2.1	54.44	"	"	10500	29700	31.5	900	2.6
24	1190	1.95	60.40	"	"	11100	31400	28.5	1000	2.3
20	1430	1.6	72.15	"	"	12000	34000	24	1190	1.95
18	1590	1.45	80.05	"	"	12600	35600	21.5	1330	1.75
15.5	1840	1.25	93.44	"	"	13500	38200	18.5	1540	1.5
14	2000	1.15	103.7	"	"	14100	39900	16.5	1730	1.35
13	2200	1.05	113.1	"	"	14600	41300	15.5	1840	1.25
11.5	2450	0.94	125.5	"	"	15300	43300	14	2000	1.15
10.5	2700	0.85	140.8	BF60Z-../D11SA4	151	15300	43300	12.5	2250	1.0
17.5	1630	3.2	81.82	BF70-../D11SA4	214	12800	41300	21	1360	3.8
15	1910	2.7	95.46	"	"	14000	43700	18	1590	3.3
13.5	2100	2.5	105.2	"	"	14700	45100	16.5	1730	3.0


P = 3 кВт


50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
12	2350	2.2	122.7	BF70-../D11SA4	"	16100	47700	14	2000	2.6
11	2600	2.0	133.0	BF70Z-../D11SA4	241	16100	47700	13	2200	2.4
9.3	3050	1.7	154.0	"	"	16100	47700	11.5	2450	2.1
8.0	3550	1.45	179.7	"	"	16100	47700	9.6	2950	1.75
7.2	3950	1.3	199.7	"	"	16100	47700	8.6	3300	1.6
6.1	4650	1.1	233.0	"	"	16100	47700	7.4	3850	1.35
5.5	5200	1.0	258.7	"	"	16100	47700	6.7	4250	1.2
4.8	5900	0.88	301.8	"	"	16100	47700	5.7	5000	1.05
9.0	3150	3.0	158.5	BF80-../D11SA4	310	29000	75000	11	2600	3.7
7.7	3700	2.6	184.5	"	"	31800	75000	9.3	3050	3.1
6.8	4200	2.3	209.4	"	"	34300	75000	8.2	3450	2.8
6.0	4750	2.0	237.1	"	"	36900	75000	7.3	3900	2.4
5.3	5400	1.75	269.1	"	"	39600	75000	6.4	4450	2.1
4.9	5800	1.8	291.7	BF80Z-../D11SA4	357	39600	75000	5.9	4850	2.2
4.1	6900	1.5	347.3	"	"	39600	75000	5.0	5700	1.85
3.7	7700	1.35	394.2	"	"	39600	75000	4.4	6500	1.6
3.2	8900	1.2	450.4	"	"	39600	75000	3.8	7500	1.4
2.8	10200	1.05	511.2	"	"	39600	75000	3.4	8400	1.25
2.5	11400	0.92	583.4	"	"	39600	75000	3.0	9500	1.1
2.2	13000	0.81	662.1	"	"	39600	75000	2.6	11000	0.95
5.5	5200	3.2	259.0	BF90-../D11SA4	563	42800	120000	6.7	4250	4.0
4.8	5900	3.1	300.4	BF90Z-../D11SA4	623	42800	120000	5.7	5000	3.7
4.2	6800	2.7	343.6	"	"	42800	120000	5.0	5700	3.2
3.8	7500	2.5	382.6	"	"	42800	120000	4.5	6300	2.9
3.2	8900	2.1	456.7	"	"	42800	120000	3.8	7500	2.5
2.8	10200	1.8	508.5	"	"	42800	120000	3.4	8400	2.2
2.5	11400	1.6	591.1	"	"	42800	120000	2.9	9800	1.9
2.2	13000	1.4	658.1	"	"	42800	120000	2.6	11000	1.7
1.9	15000	1.25	759.0	"	"	42800	120000	2.3	12400	1.5
1.7	16800	1.1	845.1	"	"	42800	120000	2.1	13600	1.35
1.5	17500	1.05	976.1	BF90G50-../D11SA4	633	42800	120000	1.8	14300	1.3
1.4	19000	0.97	1043	"	"	42800	120000	1.7	15400	1.2
1.2	22200	0.83	1204	"	"	42800	120000	1.5	17400	1.05


P = 4 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
225	169	1.55	6.34	BF30-../D11MA4	66	2400	-	270	141	1.85
176	215	1.35	8.07	"	"	2650	-	215	177	1.6
143	265	1.2	9.99	"	"	2850	-	172	220	1.45
110	345	1.05	12.91	"	"	3050	-	133	285	1.3
89	425	0.96	16.00	"	"	3250	-	107	355	1.15
81	470	1.0	17.65	"	"	3300	-	97	390	1.25
74	510	0.98	19.41	"	"	3400	-	89	425	1.2
65	580	0.91	21.85	"	"	3500	-	79	480	1.1
60	630	0.88	24.03	"	"	3600	-	72	530	1.05
245	155	2.2	5.87	BF40-../D11MA4	80	3550	-	295	129	2.6
187	200	1.85	7.62	"	"	3900	-	225	169	2.2
150	250	1.65	9.48	"	"	4150	-	181	210	2.0
121	315	1.5	11.79	"	"	4450	-	146	260	1.8
95	400	1.3	15.02	"	"	4800	-	114	335	1.55
82	465	1.35	17.35	"	"	4950	-	99	385	1.65
75	500	1.35	19.09	"	"	5100	-	90	420	1.6
66	570	1.25	21.60	"	"	5200	-	80	475	1.5
60	630	1.15	23.77	"	"	5400	-	72	530	1.4
53	720	1.1	26.86	"	"	5600	-	64	590	1.3
48.5	780	1.05	29.55	"	"	5800	-	58	650	1.25

P = 4 кВт



50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
42	900	0.95	34.21	BF40-../D11MA4	"	6000	-	50	760	1.15
38	1000	0.89	37.64	"	"	6200	-	45.5	830	1.1
34.5	1100	0.82	41.42	"	"	6500	-	41.5	920	0.98
185	205	2.8	7.71	BF50-../D11MA4	110	5100	-	225	169	3.3
133	285	2.4	10.68	"	"	5600	-	161	235	2.9
97	390	2.0	14.65	"	"	6100	-	117	325	2.4
86	440	2.2	16.70	"	"	6200	-	103	370	2.6
77	495	2.0	18.68	"	"	6400	-	92	415	2.4
62	610	1.8	23.14	"	"	6800	-	74	510	2.2
55	690	1.7	25.88	"	"	7100	-	67	570	2.0
45	840	1.5	31.73	"	"	7500	-	54	700	1.8
40.5	940	1.4	35.49	"	"	7800	-	48.5	780	1.65
34	1120	1.15	42.15	"	"	8500	-	41	930	1.4
30.5	1250	1.05	47.14	"	"	8900	-	36.5	1040	1.25
25	1520	0.86	56.86	"	"	9300	-	30.5	1250	1.05
100	380	3.1	14.24	BF60-../D11MA4	141	7100	20000	121	315	3.8
84	450	3.2	16.96	"	"	7300	20600	101	375	3.9
76	500	3.0	18.81	"	"	7600	21500	91	415	3.7
63	600	2.8	22.58	"	"	8000	22600	76	500	3.3
57	670	2.6	25.05	"	"	8200	23200	69	550	3.2
46	830	2.3	31.20	"	"	8800	24900	55	690	2.8
41.5	920	2.2	34.62	"	"	9100	25700	49.5	770	2.6
34.5	1100	1.95	41.60	"	"	9600	27100	41.5	920	2.3
31	1230	1.8	46.16	"	"	9900	28000	37.5	1010	2.2
26.5	1440	1.6	54.44	"	"	10500	29700	31.5	1210	1.9
24	1590	1.45	60.40	"	"	11100	31400	28.5	1340	1.7
20	1910	1.2	72.15	"	"	12000	34000	24	1590	1.45
18	2100	1.1	80.05	"	"	12600	35600	21.5	1770	1.3
15.5	2450	0.94	93.44	"	"	13500	38200	18.5	2050	1.1
14	2700	0.85	103.7	"	"	14100	39900	16.5	2300	1.0
23	1660	3.1	61.94	BF70-../D11MA4	220	10800	37400	28	1360	3.8
20	1910	2.7	72.26	"	"	12000	39600	24	1590	3.3
17.5	2150	2.4	81.82	"	"	12800	41300	21	1810	2.9
15	2500	2.1	95.46	"	"	14000	43700	18	2100	2.5
13.5	2800	1.85	105.2	"	"	14700	45100	16.5	2300	2.3
12	3150	1.65	122.7	"	"	16100	47700	14	2700	1.95
11	3450	1.5	133.0	BF70Z-../D11MA4	247	16100	47700	13	2900	1.8
9.3	4100	1.25	154.0	"	"	16100	47700	11.5	3300	1.6
8.0	4750	1.1	179.7	"	"	16100	47700	9.6	3950	1.3
7.2	5300	0.98	199.7	"	"	16100	47700	8.6	4400	1.2
6.1	6200	0.84	233.0	"	"	16100	47700	7.4	5100	1.0
12	3150	3.0	122.4	BF80-../D11MA4	316	24500	75000	14	2700	3.5
10.5	3600	2.6	139.7	"	"	26700	75000	12.5	3050	3.1
9.0	4200	2.3	158.5	"	"	29000	75000	11	3450	2.8
7.7	4950	1.9	184.5	"	"	31800	75000	9.3	4100	2.3
6.8	5600	1.7	209.4	"	"	34300	75000	8.2	4650	2.0
6.0	6300	1.5	237.1	"	"	36900	75000	7.3	5200	1.85
5.3	7200	1.3	269.1	"	"	39600	75000	6.4	5900	1.6
4.9	7700	1.35	291.7	BF80Z-../D11MA4	363	39600	75000	5.9	6400	1.65
4.1	9300	1.15	347.3	"	"	39600	75000	5.0	7600	1.4
3.7	10300	1.0	394.2	"	"	39600	75000	4.4	8600	1.2
3.2	11900	0.88	450.4	"	"	39600	75000	3.8	10000	1.05
7.2	5300	3.2	198.8	BF90-../D11MA4	569	36000	111300	8.7	4350	3.9
6.2	6100	2.8	232.6	"	"	39900	118300	7.4	5100	3.3
5.5	6900	2.4	259.0	"	"	42800	120000	6.7	5700	2.9
5.3	7200	2.6	269.8	BF90Z-../D11MA4	629	42800	120000	6.4	5900	3.1
4.8	7900	2.3	300.4	"	"	42800	120000	5.7	6700	2.8
4.2	9000	2.1	343.6	"	"	42800	120000	5.0	7600	2.4


P = 4 кВт


50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
3.8	10000	1.85	382.6	BF90Z-../D11MA4	"	42800	120000	4.5	8400	2.2
3.2	11900	1.55	456.7	"	"	42800	120000	3.8	10000	1.85
2.8	13600	1.35	508.5	"	"	42800	120000	3.4	11200	1.65
2.5	15200	1.2	591.1	"	"	42800	120000	2.9	13100	1.4
2.2	17300	1.05	658.1	"	"	42800	120000	2.6	14600	1.25
1.9	20100	0.92	759.0	"	"	42800	120000	2.3	16600	1.1
1.7	22400	0.83	845.1	"	"	42800	120000	2.1	18100	1.0

P = 5.5 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
225	230	1.15	6.34	BF30-../D11LA4	78	2400	-	270	194	1.35
176	295	0.97	8.07	"	"	2650	-	215	240	1.2
143	365	0.88	9.99	"	"	2850	-	172	305	1.05
245	210	1.6	5.87	BF40-../D11LA4	92	3550	-	295	178	1.9
187	280	1.3	7.62	"	"	3900	-	225	230	1.6
150	350	1.2	9.48	"	"	4150	-	181	290	1.45
121	430	1.1	11.79	"	"	4450	-	146	355	1.3
95	550	0.95	15.02	"	"	4800	-	114	460	1.15
82	640	0.99	17.35	"	"	4950	-	99	530	1.2
75	700	0.95	19.09	"	"	5100	-	90	580	1.15
66	790	0.89	21.60	"	"	5200	-	80	650	1.1
60	870	0.85	23.77	"	"	5400	-	72	720	1.0
265	198	2.5	5.38	BF50-../D11LA4	122	4500	-	320	164	3.0
185	280	2.0	7.71	"	"	5100	-	225	230	2.5
133	390	1.75	10.68	"	"	5600	-	161	325	2.1
97	540	1.45	14.65	"	"	6100	-	117	445	1.8
86	610	1.55	16.70	"	"	6200	-	103	500	1.9
77	680	1.5	18.68	"	"	6400	-	92	570	1.75
62	840	1.3	23.14	"	"	6800	-	74	700	1.6
55	950	1.25	25.88	"	"	7100	-	67	780	1.5
45	1160	1.1	31.73	"	"	7500	-	54	970	1.3
40.5	1290	1.0	35.49	"	"	7800	-	48.5	1080	1.2
34	1540	0.84	42.15	"	"	8500	-	41	1280	1.0
184	285	3.0	7.74	BF60-../D11LA4	153	6000	16900	225	230	3.8
138	380	2.7	10.31	"	"	6500	18400	166	315	3.2
100	520	2.3	14.24	"	"	7100	20000	121	430	2.8
84	620	2.3	16.96	"	"	7300	20600	101	520	2.8
76	690	2.2	18.81	"	"	7600	21500	91	570	2.7
63	830	2.0	22.58	"	"	8000	22600	76	690	2.4
57	920	1.9	25.05	"	"	8200	23200	69	760	2.3
46	1140	1.65	31.20	"	"	8800	24900	55	950	2.0
41.5	1260	1.6	34.62	"	"	9100	25700	49.5	1060	1.85
34.5	1520	1.4	41.60	"	"	9600	27100	41.5	1260	1.7
31	1690	1.3	46.16	"	"	9900	28000	37.5	1400	1.6
26.5	1980	1.15	54.44	"	"	10500	29700	31.5	1660	1.4
24	2150	1.05	60.40	"	"	11100	31400	28.5	1840	1.25
20	2600	0.88	72.15	"	"	12000	34000	24	2150	1.05
33.5	1560	3.3	43.02	BF70-../D11LA4	232	8700	32800	40	1310	4.0
30	1750	3.0	47.82	"	"	9100	34000	36	1450	3.6
25.5	2050	2.5	55.79	"	"	10200	36000	31	1690	3.1
23	2250	2.3	61.94	"	"	10800	37400	28	1870	2.8
20	2600	2.0	72.26	"	"	12000	39600	24	2150	2.4
17.5	3000	1.75	81.82	"	"	12800	41300	21	2500	2.1
15	3500	1.5	95.46	"	"	14000	43700	18	2900	1.8
13.5	3850	1.35	105.2	"	"	14700	45100	16.5	3150	1.65
12	4350	1.2	122.7	"	"	16100	47700	14	3750	1.4


P = 5.5 кВт



50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
11	4750	1.1	133.0	BF70Z-../D11LA4	258	16100	47700	13	4000	1.3
9.3	5600	0.93	154.0	"	"	16100	47700	11.5	4550	1.15
8.0	6500	0.8	179.7	"	"	16100	47700	9.6	5400	0.96
17.5	3000	3.2	83.16	BF80-../D11LA4	328	18400	65100	21	2500	3.8
15.5	3350	2.8	94.38	"	"	20300	68500	18.5	2800	3.4
13.5	3850	2.5	107.9	"	"	22400	72300	16	3250	2.9
12	4350	2.2	122.4	"	"	24500	75000	14	3750	2.5
10.5	5000	1.9	139.7	"	"	26700	75000	12.5	4200	2.3
9.0	5800	1.65	158.5	"	"	29000	75000	11	4750	2.0
7.7	6800	1.4	184.5	"	"	31800	75000	9.3	5600	1.7
6.8	7700	1.25	209.4	"	"	34300	75000	8.2	6400	1.5
6.0	8700	1.1	237.1	"	"	36900	75000	7.3	7100	1.35
5.3	9900	0.96	269.1	"	"	39600	75000	6.4	8200	1.15
4.9	10700	0.98	291.7	BF80Z-../D11LA4	375	39600	75000	5.9	8900	1.2
4.1	12800	0.82	347.3	"	"	39600	75000	5.0	10500	1.0
9.2	5700	2.9	154.8	BF90-../D11LA4	581	30100	100800	11.5	4550	3.7
8.0	6500	2.6	178.6	"	"	33400	106700	9.6	5400	3.1
7.2	7200	2.3	198.8	"	"	36000	111300	8.7	6000	2.8
6.2	8400	2.0	232.6	"	"	39900	118300	7.4	7000	2.4
5.5	9500	1.75	259.0	"	"	42800	120000	6.7	7800	2.2
5.3	9900	1.85	269.8	BF90Z-../D11LA4	641	42800	120000	6.4	8200	2.3
4.8	10900	1.7	300.4	"	"	42800	120000	5.7	9200	2.0
4.2	12500	1.5	343.6	"	"	42800	120000	5.0	10500	1.75
3.8	13800	1.35	382.6	"	"	42800	120000	4.5	11600	1.6
3.2	16400	1.15	456.7	"	"	42800	120000	3.8	13800	1.35
2.8	18700	0.99	508.5	"	"	42800	120000	3.4	15400	1.2
2.5	21000	0.88	591.1	"	"	42800	120000	2.9	18100	1.0

P = 7.5 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
265	270	1.85	5.38	BF50-../D13MA4	133	4500	-	320	220	2.3
185	385	1.45	7.71	"	"	5100	-	225	315	1.8
133	530	1.3	10.68	"	"	5600	-	161	440	1.55
97	730	1.1	14.65	"	"	6100	-	117	610	1.3
86	830	1.15	16.70	"	"	6200	-	103	690	1.4
77	930	1.1	18.68	"	"	6400	-	92	770	1.3
62	1150	0.96	23.14	"	"	6800	-	74	960	1.15
55	1300	0.9	25.88	"	"	7100	-	67	1060	1.1
45	1590	0.8	31.73	"	"	7500	-	54	1320	0.96
275	260	2.9	5.22	BF60-../D13MA4	166	5200	14800	330	215	3.5
184	385	2.3	7.74	"	"	6000	16900	225	315	2.8
138	510	2.0	10.31	"	"	6500	18400	166	430	2.4
100	710	1.7	14.24	"	"	7100	20000	121	590	2.0
84	850	1.7	16.96	"	"	7300	20600	101	700	2.1
76	940	1.6	18.81	"	"	7600	21500	91	780	1.95
63	1130	1.45	22.58	"	"	8000	22600	76	940	1.75
57	1250	1.4	25.05	"	"	8200	23200	69	1030	1.7
46	1550	1.25	31.20	"	"	8800	24900	55	1300	1.45
41.5	1720	1.15	34.62	"	"	9100	25700	49.5	1440	1.4
34.5	2050	1.05	41.60	"	"	9600	27100	41.5	1720	1.25
31	2300	0.97	46.16	"	"	9900	28000	37.5	1910	1.15
26.5	2700	0.85	54.44	"	"	10500	29700	31.5	2250	1.0
45	1590	3.3	31.84	BF70-../D13MA4	245	7700	30000	54	1320	3.9
39	1830	2.8	36.88	"	"	7900	31100	46.5	1540	3.4
33.5	2100	2.5	43.02	"	"	8700	32800	40	1790	2.9


P = 7.5 кВт


50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
30	2350	2.2	47.82	BF70-../D13MA4	"	9100	34000	36	1980	2.6
25.5	2800	1.85	55.79	"	"	10200	36000	31	2300	2.3
23	3100	1.7	61.94	"	"	10800	37400	28	2550	2.0
20	3550	1.45	72.26	"	"	12000	39600	24	2950	1.75
17.5	4050	1.3	81.82	"	"	12800	41300	21	3400	1.55
15	4750	1.1	95.46	"	"	14000	43700	18	3950	1.3
13.5	5300	0.98	105.2	"	"	14700	45100	16.5	4300	1.2
12	5900	0.88	122.7	"	"	16100	47700	14	5100	1.0
11	6500	0.8	133.0	BF70Z-../D13MA4	270	16100	47700	13	5500	0.95
26.5	2700	3.3	53.86	BF80-../D13MA4	341	14000	55800	32	2200	4.1
23.5	3000	3.1	61.55	"	"	14800	58100	28	2550	3.6
20.5	3450	2.8	69.86	"	"	15900	60600	24.5	2900	3.3
17.5	4050	2.3	83.16	"	"	18400	65100	21	3400	2.8
15.5	4600	2.1	94.38	"	"	20300	68500	18.5	3850	2.5
13.5	5300	1.8	107.9	"	"	22400	72300	16	4450	2.1
12	5900	1.6	122.4	"	"	24500	75000	14	5100	1.85
10.5	6800	1.4	139.7	"	"	26700	75000	12.5	5700	1.65
9.0	7900	1.2	158.5	"	"	29000	75000	11	6500	1.45
7.7	9300	1.0	184.5	"	"	31800	75000	9.3	7700	1.25
6.8	10500	0.9	209.4	"	"	34300	75000	8.2	8700	1.1
6.0	11900	0.8	237.1	"	"	36900	75000	7.3	9800	0.97
13.5	5300	3.2	107.5	BF90-../D13MA4	593	22300	86900	16	4450	3.8
12	5900	2.8	119.7	"	"	24500	90800	14.5	4900	3.4
10.5	6800	2.5	139.1	"	"	27700	96300	12.5	5700	2.9
9.2	7700	2.2	154.8	"	"	30100	100800	11.5	6200	2.7
8.0	8900	1.9	178.6	"	"	33400	106700	9.6	7400	2.3
7.2	9900	1.7	198.8	"	"	36000	111300	8.7	8200	2.0
6.2	11500	1.45	232.6	"	"	39900	118300	7.4	9600	1.75
5.5	13000	1.3	259.0	"	"	42800	120000	6.7	10600	1.6
5.3	13500	1.35	269.8	BF90Z-../D13MA4	654	42800	120000	6.4	11100	1.65
4.8	14900	1.25	300.4	"	"	42800	120000	5.7	12500	1.5
4.2	17000	1.1	343.6	"	"	42800	120000	5.0	14300	1.3
3.8	18800	0.98	382.6	"	"	42800	120000	4.5	15900	1.15
3.2	22300	0.83	456.7	"	"	42800	120000	3.8	18800	0.98

P = 9.5 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
265	340	1.45	5.38	BF50-../D13LA4	136	4500	-	320	280	1.8
185	490	1.15	7.71	"	"	5100	-	225	400	1.4
133	680	0.99	10.68	"	"	5600	-	161	560	1.2
97	930	0.85	14.65	"	"	6100	-	117	770	1.05
86	1050	0.9	16.70	"	"	6200	-	103	880	1.1
77	1170	0.86	18.68	"	"	6400	-	92	980	1.0
275	325	2.3	5.22	BF60-../D13LA4	169	5200	14800	330	270	2.8
184	490	1.75	7.74	"	"	6000	16900	225	400	2.2
138	650	1.55	10.31	"	"	6500	18400	166	540	1.9
100	900	1.3	14.24	"	"	7100	20000	121	740	1.6
84	1080	1.35	16.96	"	"	7300	20600	101	890	1.65
76	1190	1.3	18.81	"	"	7600	21500	91	990	1.55
63	1440	1.15	22.58	"	"	8000	22600	76	1190	1.4
57	1590	1.1	25.05	"	"	8200	23200	69	1310	1.3
46	1970	0.96	31.20	"	"	8800	24900	55	1640	1.15
41.5	2150	0.92	34.62	"	"	9100	25700	49.5	1830	1.1
34.5	2600	0.82	41.60	"	"	9600	27100	41.5	2150	0.99
58	1560	3.2	24.55	BF70-../D13LA4	248	7000	27700	70	1290	3.9
53	1710	3.0	27.29	"	"	7000	28400	63	1440	3.6


P = 9.5 кВт



50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
45	2000	2.6	31.84	BF70-../D13LA4	"	7700	30000	54	1680	3.1
39	2300	2.3	36.88	"	"	7900	31100	46.5	1950	2.7
33.5	2700	1.95	43.02	"	"	8700	32800	40	2250	2.3
30	3000	1.75	47.82	"	"	9100	34000	36	2500	2.1
25.5	3550	1.45	55.79	"	"	10200	36000	31	2900	1.8
23	3900	1.35	61.94	"	"	10800	37400	28	3200	1.65
20	4500	1.15	72.26	"	"	12000	39600	24	3750	1.4
17.5	5100	1.0	81.82	"	"	12800	41300	21	4300	1.2
15	6000	0.87	95.46	"	"	14000	43700	18	5000	1.05
30	3000	2.9	47.46	BF80-../D13LA4	344	13400	53700	36.5	2450	3.5
26.5	3400	2.6	53.86	"	"	14000	55800	32	2800	3.2
23.5	3850	2.4	61.55	"	"	14800	58100	28	3200	2.9
20.5	4400	2.2	69.86	"	"	15900	60600	24.5	3700	2.6
17.5	5100	1.85	83.16	"	"	18400	65100	21	4300	2.2
15.5	5800	1.65	94.38	"	"	20300	68500	18.5	4900	1.95
13.5	6700	1.4	107.9	"	"	22400	72300	16	5600	1.7
12	7500	1.25	122.4	"	"	24500	75000	14	6400	1.5
10.5	8600	1.1	139.7	"	"	26700	75000	12.5	7200	1.3
9.0	10000	0.95	158.5	"	"	29000	75000	11	8200	1.15
7.7	11700	0.81	184.5	"	"	31800	75000	9.3	9700	0.98
18	5000	3.3	80.85	BF90-../D13LA4	596	17500	77500	21.5	4200	3.9
16	5600	3.0	90.02	"	"	18900	80600	19	4750	3.5
13.5	6700	2.5	107.5	"	"	22300	86900	16	5600	3.0
12	7500	2.2	119.7	"	"	24500	90800	14.5	6200	2.7
10.5	8600	1.95	139.1	"	"	27700	96300	12.5	7200	2.3
9.2	9800	1.7	154.8	"	"	30100	100800	11.5	7800	2.2
8.0	11300	1.5	178.6	"	"	33400	106700	9.6	9400	1.8
7.2	12600	1.35	198.8	"	"	36000	111300	8.7	10400	1.6
6.2	14600	1.15	232.6	"	"	39900	118300	7.4	12200	1.4
5.5	16400	1.0	259.0	"	"	42800	120000	6.7	13500	1.25
5.3	17100	1.1	269.8	BF90Z-../D13LA4	657	42800	120000	6.4	14100	1.3
4.8	18900	0.98	300.4	"	"	42800	120000	5.7	15900	1.15
4.2	21600	0.86	343.6	"	"	42800	120000	5.0	18100	1.0

P = 11 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
275	380	1.3	5.38	BF50-../D16MA4	181	4500	-	330	315	1.6
190	550	1.05	7.71	"	"	5100	-	230	455	1.25
137	760	0.89	10.68	"	"	5600	-	165	630	1.05
88	1190	0.8	16.70	"	"	6200	-	106	990	0.96
280	375	2.0	5.22	BF60-../D16MA4	214	5200	14800	340	305	2.5
189	550	1.6	7.74	"	"	6000	16900	230	455	1.9
142	730	1.4	10.31	"	"	6500	18400	171	610	1.65
103	1010	1.2	14.24	"	"	7100	20000	124	840	1.4
87	1200	1.2	16.96	"	"	7300	20600	104	1010	1.45
78	1340	1.15	18.81	"	"	7600	21500	94	1110	1.35
65	1610	1.05	22.58	"	"	8000	22600	78	1340	1.25
59	1780	0.97	25.05	"	"	8200	23200	71	1470	1.2
47	2200	0.86	31.20	"	"	8800	24900	57	1840	1.05
42.5	2450	0.81	34.62	"	"	9100	25700	51	2050	0.97
70	1500	3.1	21.04	BF70-../D16MA4	297	6400	26300	84	1250	3.7
60	1750	2.9	24.55	"	"	7000	27700	72	1450	3.5
54	1940	2.7	27.29	"	"	7000	28400	65	1610	3.2
46	2250	2.3	31.84	"	"	7700	30000	56	1870	2.8
40	2600	2.0	36.88	"	"	7900	31100	48	2150	2.4


P = 11 кВт


50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
34	3050	1.7	43.02	BF70-../D16MA4	"	8700	32800	41	2550	2.0
31	3350	1.55	47.82	"	"	9100	34000	37	2800	1.85
26.5	3950	1.3	55.79	"	"	10200	36000	32	3250	1.6
24	4350	1.2	61.94	"	"	10800	37400	28.5	3650	1.4
20.5	5100	1.0	72.26	"	"	12000	39600	24.5	4250	1.2
18	5800	0.9	81.82	"	"	12800	41300	22	4750	1.1
48.5	2150	3.3	30.21	BF80-../D16MA4	393	12300	47900	59	1780	4.0
43.5	2400	3.2	33.61	"	"	11700	48400	53	1980	3.9
38.5	2700	3.0	38.14	"	"	12200	50300	46.5	2250	3.6
31	3350	2.6	47.46	"	"	13400	53700	37.5	2800	3.1
27.5	3800	2.4	53.86	"	"	14000	55800	33	3150	2.8
24	4350	2.1	61.55	"	"	14800	58100	29	3600	2.6
21	5000	1.9	69.86	"	"	15900	60600	25.5	4100	2.3
18	5800	1.65	83.16	"	"	18400	65100	21.5	4850	1.95
15.5	6700	1.4	94.38	"	"	20300	68500	19	5500	1.75
14	7500	1.25	107.9	"	"	22400	72300	16.5	6300	1.5
12	8700	1.1	122.4	"	"	24500	75000	14.5	7200	1.3
10.5	10000	0.95	139.7	"	"	26700	75000	13	8000	1.2
9.3	11200	0.85	158.5	"	"	29000	75000	11.5	9100	1.05
21	5000	3.2	70.69	BF90-../D16MA4	640	16800	74700	25	4200	3.8
18.5	5600	3.0	80.85	"	"	17500	77500	22	4750	3.5
16.5	6300	2.7	90.02	"	"	18900	80600	20	5200	3.2
14	7500	2.2	107.5	"	"	22300	86900	16.5	6300	2.7
12.5	8400	2.0	119.7	"	"	24500	90800	15	7000	2.4
10.5	10000	1.7	139.1	"	"	27700	96300	13	8000	2.1
9.5	11000	1.55	154.8	"	"	30100	100800	11.5	9100	1.85
8.2	12800	1.3	178.6	"	"	33400	106700	9.9	10600	1.6
7.4	14100	1.2	198.8	"	"	36000	111300	8.9	11800	1.4
6.3	16600	1.0	232.6	"	"	39900	118300	7.6	13800	1.2
5.7	18400	0.91	259.0	"	"	42800	120000	6.8	15400	1.1
5.5	19100	0.97	269.8	BF90Z-../D16MA4	702	42800	120000	6.6	15900	1.15
4.9	21400	0.86	300.4	"	"	42800	120000	5.9	17800	1.05

P = 15 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
275	520	0.96	5.38	BF50-../D16LA4	194	4500	-	330	430	1.15
280	510	1.5	5.22	BF60-../D16LA4	227	5200	14800	340	420	1.8
189	750	1.15	7.74	"	"	6000	16900	230	620	1.4
142	1000	1.0	10.31	"	"	6500	18400	171	830	1.2
103	1390	0.86	14.24	"	"	7100	20000	124	1150	1.05
87	1640	0.88	16.96	"	"	7300	20600	104	1370	1.05
78	1830	0.83	18.81	"	"	7600	21500	94	1520	1.0
98	1460	2.5	14.90	BF70-../D16LA4	310	5900	24000	119	1200	3.0
84	1700	2.5	17.39	"	"	6200	25000	102	1400	3.0
70	2000	2.3	21.04	"	"	6400	26300	84	1700	2.7
60	2350	2.1	24.55	"	"	7000	27700	72	1980	2.5
54	2650	1.95	27.29	"	"	7000	28400	65	2200	2.4
46	3100	1.7	31.84	"	"	7700	30000	56	2550	2.0
40	3550	1.45	36.88	"	"	7900	31100	48	2950	1.75
34	4200	1.25	43.02	"	"	8700	32800	41	3450	1.5
31	4600	1.15	47.82	"	"	9100	34000	37	3850	1.35
26.5	5400	0.96	55.79	"	"	10200	36000	32	4450	1.15
24	5900	0.88	61.94	"	"	10800	37400	28.5	5000	1.05


P = 15 кВт



50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
89	1600	3.3	16.49	BF80-../D16LA4	406	11400	41400	107	1330	4.0
63	2250	2.8	23.29	"	"	11800	44900	76	1880	3.4
48.5	2950	2.4	30.21	"	"	12300	47900	59	2400	3.0
43.5	3250	2.4	33.61	"	"	11700	48400	53	2700	2.9
38.5	3700	2.2	38.14	"	"	12200	50300	46.5	3050	2.6
31	4600	1.85	47.46	"	"	13400	53700	37.5	3800	2.3
27.5	5200	1.7	53.86	"	"	14000	55800	33	4300	2.1
24	5900	1.6	61.55	"	"	14800	58100	29	4900	1.9
21	6800	1.4	69.86	"	"	15900	60600	25.5	5600	1.7
18	7900	1.2	83.16	"	"	18400	65100	21.5	6600	1.45
15.5	9200	1.05	94.38	"	"	20300	68500	19	7500	1.25
14	10200	0.93	107.9	"	"	22400	72300	16.5	8600	1.1
12	11900	0.8	122.4	"	"	24500	75000	14.5	9800	0.97
31.5	4500	3.1	46.43	BF90-../D16LA4	654	13800	65500	38	3750	3.8
28.5	5000	2.9	51.70	"	"	14600	67800	34.5	4150	3.5
23	6200	2.5	63.49	"	"	15800	72000	28	5100	3.0
21	6800	2.3	70.69	"	"	16800	74700	25	5700	2.8
18.5	7700	2.1	80.85	"	"	17500	77500	22	6500	2.5
16.5	8600	1.95	90.02	"	"	18900	80600	20	7100	2.4
14	10200	1.65	107.5	"	"	22300	86900	16.5	8600	1.95
12.5	11400	1.45	119.7	"	"	24500	90800	15	9500	1.75
10.5	13600	1.25	139.1	"	"	27700	96300	13	11000	1.55
9.5	15000	1.1	154.8	"	"	30100	100800	11.5	12400	1.35
8.2	17400	0.97	178.6	"	"	33400	106700	9.9	14400	1.15
7.4	19300	0.87	198.8	"	"	36000	111300	8.9	16000	1.05

P = 18.5 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
280	630	1.2	5.22	BF60-../D16XA4	237	5200	14800	340	510	1.5
189	930	0.93	7.74	"	"	6000	16900	230	760	1.15
142	1240	0.82	10.31	"	"	6500	18400	171	1030	0.98
98	1800	2.0	14.90	BF70-../D16XA4	320	5900	24000	119	1480	2.5
84	2100	2.0	17.39	"	"	6200	25000	102	1730	2.5
70	2500	1.85	21.04	"	"	6400	26300	84	2100	2.2
60	2900	1.75	24.55	"	"	7000	27700	72	2450	2.1
54	3250	1.6	27.29	"	"	7000	28400	65	2700	1.95
46	3800	1.35	31.84	"	"	7700	30000	56	3150	1.65
40	4400	1.2	36.88	"	"	7900	31100	48	3650	1.4
34	5100	1.0	43.02	"	"	8700	32800	41	4300	1.2
31	5600	0.93	47.82	"	"	9100	34000	37	4750	1.1
89	1980	2.7	16.49	BF80-../D16XA4	416	11400	41400	107	1650	3.2
63	2800	2.3	23.29	"	"	11800	44900	76	2300	2.7
48.5	3600	2.0	30.21	"	"	12300	47900	59	2950	2.4
43.5	4050	1.9	33.61	"	"	11700	48400	53	3300	2.4
38.5	4550	1.75	38.14	"	"	12200	50300	46.5	3750	2.2
31	5600	1.55	47.46	"	"	13400	53700	37.5	4700	1.85
27.5	6400	1.4	53.86	"	"	14000	55800	33	5300	1.7
24	7300	1.25	61.55	"	"	14800	58100	29	6000	1.55
21	8400	1.15	69.86	"	"	15900	60600	25.5	6900	1.4
18	9800	0.97	83.16	"	"	18400	65100	21.5	8200	1.15
15.5	11300	0.84	94.38	"	"	20300	68500	19	9200	1.05
31.5	5600	2.5	46.43	BF90-../D16XA4	664	13800	65500	38	4600	3.1
28.5	6100	2.4	51.70	"	"	14600	67800	34.5	5100	2.8
23	7600	2.0	63.49	"	"	15800	72000	28	6300	2.4
21	8400	1.9	70.69	"	"	16800	74700	25	7000	2.3


P = 18.5 кВт


50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
18.5	9500	1.75	80.85	BF90-../D16XA4	"	17500	77500	22	8000	2.1
16.5	10700	1.55	90.02	"	"	18900	80600	20	8800	1.9
14	12600	1.35	107.5	"	"	22300	86900	16.5	10700	1.55
12.5	14100	1.2	119.7	"	"	24500	90800	15	11700	1.45
10.5	16800	1.0	139.1	"	"	27700	96300	13	13500	1.25
9.5	18500	0.91	154.8	"	"	30100	100800	11.5	15300	1.1

P = 22 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
142	1470	1.7	10.32	BF70-../D18LA4	377	4600	18700	171	1220	2.1
122	1720	1.7	12.04	"	"	4900	19700	147	1420	2.1
98	2100	1.75	14.90	"	"	5900	24000	119	1760	2.1
84	2500	1.7	17.39	"	"	6200	25000	102	2050	2.1
70	3000	1.55	21.04	"	"	6400	26300	84	2500	1.85
60	3500	1.45	24.55	"	"	7000	27700	72	2900	1.75
54	3850	1.35	27.29	"	"	7000	28400	65	3200	1.65
46	4550	1.15	31.84	"	"	7700	30000	56	3750	1.4
40	5200	1.0	36.88	"	"	7900	31100	48	4350	1.2
34	6100	0.85	43.02	"	"	8700	32800	41	5100	1.0
128	1640	2.2	11.42	BF80-../D18LA4	473	8900	32200	155	1350	2.7
89	2350	2.3	16.49	"	"	11400	41400	107	1960	2.7
63	3300	1.9	23.29	"	"	11800	44900	76	2750	2.3
48.5	4300	1.65	30.21	"	"	12300	47900	59	3550	2.0
43.5	4800	1.6	33.61	"	"	11700	48400	53	3950	1.95
38.5	5400	1.5	38.14	"	"	12200	50300	46.5	4500	1.8
31	6700	1.3	47.46	"	"	13400	53700	37.5	5600	1.55
27.5	7600	1.2	53.86	"	"	14000	55800	33	6300	1.4
24	8700	1.05	61.55	"	"	14800	58100	29	7200	1.3
21	10000	0.95	69.86	"	"	15900	60600	25.5	8200	1.15
18	11600	0.82	83.16	"	"	18400	65100	21.5	9700	0.98
61	3400	3.3	23.95	BF90-../D18LA4	725	11100	54300	74	2800	4.0
43.5	4800	2.7	33.71	"	"	11900	59300	53	3950	3.3
39	5300	2.5	37.54	"	"	12700	61500	47	4450	3.0
31.5	6600	2.1	46.43	"	"	13800	65500	38	5500	2.6
28.5	7300	2.0	51.70	"	"	14600	67800	34.5	6000	2.4
23	9100	1.7	63.49	"	"	15800	72000	28	7500	2.1
21	10000	1.6	70.69	"	"	16800	74700	25	8400	1.9
18.5	11300	1.45	80.85	"	"	17500	77500	22	9500	1.75
16.5	12700	1.3	90.02	"	"	18900	80600	20	10500	1.6
14	15000	1.1	107.5	"	"	22300	86900	16.5	12700	1.3
12.5	16800	1.0	119.7	"	"	24500	90800	15	14000	1.2
10.5	20000	0.84	139.1	"	"	27700	96300	13	16100	1.05

P = 30 кВт




50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
142	2000	1.25	10.32	BF70-../D18XA4	395	4600	18700	171	1670	1.5
122	2300	1.3	12.04	"	"	4900	19700	147	1940	1.5
98	2900	1.25	14.90	"	"	5900	24000	119	2400	1.5
84	3400	1.25	17.39	"	"	6200	25000	102	2800	1.5
70	4050	1.15	21.04	"	"	6400	26300	84	3400	1.35
60	4750	1.05	24.55	"	"	7000	27700	72	3950	1.25
54	5300	0.98	27.29	"	"	7000	28400	65	4400	1.2
46	6200	0.84	31.84	"	"	7700	30000	56	5100	1.0
128	2200	1.65	11.42	BF80-../D18XA4	491	8900	32200	155	1840	2.0
89	3200	1.65	16.49	"	"	11400	41400	107	2650	2.0
63	4500	1.4	23.29	"	"	11800	44900	76	3750	1.7
48.5	5900	1.2	30.21	"	"	12300	47900	59	4850	1.45
43.5	6500	1.2	33.61	"	"	11700	48400	53	5400	1.45
38.5	7400	1.1	38.14	"	"	12200	50300	46.5	6100	1.3
31	9200	0.94	47.46	"	"	13400	53700	37.5	7600	1.15
27.5	10400	0.86	53.86	"	"	14000	55800	33	8600	1.05
118	2400	3.0	12.45	BF90-../D18XA4	743	8000	39700	142	2000	3.6
84	3400	3.0	17.39	"	"	10000	49500	102	2800	3.6
61	4650	2.4	23.95	"	"	11100	54300	74	3850	2.9
43.5	6500	2.0	33.71	"	"	11900	59300	53	5400	2.4
39	7300	1.8	37.54	"	"	12700	61500	47	6000	2.2
31.5	9000	1.55	46.43	"	"	13800	65500	38	7500	1.9
28.5	10000	1.45	51.70	"	"	14600	67800	34.5	8300	1.75
23	12400	1.25	63.49	"	"	15800	72000	28	10200	1.5
21	13600	1.15	70.69	"	"	16800	74700	25	11400	1.4
18.5	15400	1.05	80.85	"	"	17500	77500	22	13000	1.25
16.5	17300	0.97	90.02	"	"	18900	80600	20	14300	1.15
14	20400	0.82	107.5	"	"	22300	86900	16.5	17300	0.97

P = 37 кВт

50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
142	2450	1.05	10.32	BF70-...-K/DNF22SB4	604	4600	18700	171	2050	1.25
122	2850	1.05	12.04	"	"	4900	19700	147	2400	1.25
98	3600	1.0	14.90	"	"	5900	24000	119	2950	1.25
84	4200	1.0	17.39	"	"	6200	25000	102	3450	1.25
128	2750	1.35	11.42	BF80-...-K/DNF22SB4	700	8900	32200	155	2250	1.65
89	3950	1.35	16.49	"	"	11400	41400	107	3300	1.6
63	5600	1.15	23.29	"	"	11800	44900	76	4600	1.35
118	2950	2.4	12.45	BF90-...-K/DNF22SB4	958	8000	39700	142	2450	2.9
84	4200	2.4	17.39	"	"	10000	49500	102	3450	2.9
61	5700	1.95	23.95	"	"	11100	54300	74	4750	2.4
43.5	8100	1.6	33.71	"	"	11900	59300	53	6600	1.95
39	9000	1.45	37.54	"	"	12700	61500	47	7500	1.75
31.5	11200	1.25	46.43	"	"	13800	65500	38	9200	1.55
28.5	12300	1.15	51.70	"	"	14600	67800	34.5	10200	1.4
23	15300	1.0	63.49	"	"	15800	72000	28	12600	1.2

P = 45 кВт



50 Гц			i	Тип	m	F _{RN}	F _{RV}	60 Гц		
n ₂ 1/min	M ₂ Нм	f _B						n ₂ 1/min	M ₂ Нм	f _B
128	3350	1.1	11.42	BF80--K/DNF22MB4	730	8900	32200	155	2750	1.35
89	4800	1.1	16.49	"	"	11400	41400	107	4000	1.35
118	3600	2.0	12.45	BF90--K/DNF22MB4	988	8000	39700	142	3000	2.4
84	5100	2.0	17.39	"	"	10000	49500	102	4200	2.4
61	7000	1.6	23.95	"	"	11100	54300	74	5800	1.95
43.5	9800	1.3	33.71	"	"	11900	59300	53	8100	1.6
39	11000	1.2	37.54	"	"	12700	61500	47	9100	1.45
31.5	13600	1.05	46.43	"	"	13800	65500	38	11300	1.25