



**P = 0.55 кВт**



50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
194	24.5	3.0	7.25	<b>BK06-../D08MA4</b>	15	790	-	235	20.5	3.6
145	33	2.4	9.71	"	"	880	-	174	27.5	2.9
120	40	2.0	11.67	"	"	930	-	144	33.5	2.4
92	51	1.55	15.29	"	"	1020	-	110	43	1.85
78	60	1.35	18.00	"	"	1080	-	94	50	1.6
65	72	1.1	21.54	"	"	1150	-	78	60	1.35
54	87	0.92	26.36	"	"	1230	-	64	73	1.1
118	40.5	2.8	11.93	<b>BK10-../D08MA4</b>	27	3100	-	141	34	3.4
83	56	2.4	16.92	"	"	3700	-	100	47	2.9
76	62	3.2	18.52	"	"	4300	-	91	51	3.9
62	76	2.6	22.65	"	"	4650	-	75	63	3.2
49	96	2.1	28.76	"	"	5200	-	59	80	2.5
41	115	1.75	34.25	"	"	5600	-	49.5	95	2.1
34.5	137	1.45	40.79	"	"	6000	-	41.5	113	1.75
29	161	1.25	48.96	"	"	6400	-	34.5	135	1.5
23	200	1.0	61.68	"	"	7000	-	27.5	169	1.2
19.5	235	0.85	72.31	"	"	7000	-	23.5	196	1.0
38.5	122	2.7	36.69	<b>BK20-../D08MA4</b>	36	5400	9000	46	102	3.2
33	143	2.3	42.70	"	"	5800	9000	39.5	119	2.8
27.5	169	1.95	51.22	"	"	6300	9000	33	141	2.3
23	200	1.65	61.30	"	"	6500	9000	27.5	169	1.95
18.5	245	1.35	76.79	"	"	7500	9000	22	210	1.55
16	285	1.15	88.12	"	"	8000	9000	19.5	230	1.45
13	345	0.91	108.6	"	"	8700	9000	15.5	290	1.1
11.5	385	0.86	124.2	<b>BK20Z-../D08MA4</b>	38	8700	9000	14	315	1.05
33	141	3.2	42.89	<b>BK30-../D08MA4</b>	42	7800	12000	39.5	118	3.8
28	165	2.7	50.27	"	"	8300	12000	33.5	137	3.3
24	192	2.3	59.27	"	"	8900	12000	28.5	162	2.8
20	225	2.0	71.56	"	"	9700	12000	23.5	194	2.3
16	280	1.6	88.38	"	"	10600	12000	19.5	230	1.95
14	315	1.45	102.4	"	"	11200	12000	16.5	270	1.65
11.5	385	1.15	123.9	<b>BK30Z-../D08MA4</b>	45	11200	12000	14	315	1.45
9.7	450	1.0	145.1	"	"	11200	12000	12	365	1.25
17	265	2.9	84.36	<b>BK40-../D08MA4</b>	63	10700	17000	20	225	3.5
13.5	330	2.4	104.0	"	"	11700	17000	16.5	270	2.9
12	370	2.1	118.2	<b>BK40Z-../D08MA4</b>	67	11700	17000	14.5	305	2.6
9.8	450	1.75	143.0	"	"	11700	17000	12	365	2.1
8.3	520	1.5	169.0	"	"	11700	17000	10	435	1.8
6.7	640	1.2	211.5	"	"	11700	17000	8.0	530	1.45
5.7	740	1.05	246.6	"	"	11700	17000	6.9	610	1.3
4.9	860	0.8	289.8	"	"	11700	17000	5.8	730	0.94
12.5	355	3.0	115.4	<b>BK50Z-../D08MA4</b>	96	14100	26000	15	295	3.6
9.2	470	2.2	153.3	"	"	14100	26000	11	395	2.7
6.8	630	1.65	206.8	"	"	14100	26000	8.2	520	2.0
5.3	800	1.3	264.5	"	"	14100	26000	6.4	660	1.6
4.3	980	1.05	328.2	"	"	14100	26000	5.2	810	1.25
3.1	1290	0.89	465.1	<b>BK50G10-../D08MA4</b>	100	14100	26000	3.7	1080	1.05
2.8	1420	0.81	513.4	"	"	14100	26000	3.3	1210	0.95
6.9	760	3.0	205.0	<b>BK60Z-../D08MA4</b>	119	16600	34000	8.2	640	3.6
5.9	890	2.6	239.7	"	"	16600	34000	7.1	730	3.2
5.3	990	2.3	268.2	"	"	16600	34000	6.3	830	2.8
4.5	1160	2.0	317.7	"	"	16600	34000	5.3	990	2.3
4.0	1310	1.75	355.5	"	"	16600	34000	4.8	1090	2.1
3.5	1500	1.55	411.5	"	"	16600	34000	4.1	1280	1.8
3.1	1690	1.35	460.4	"	"	16600	34000	3.7	1410	1.65
2.9	1810	1.25	498.0	"	"	16600	34000	3.4	1540	1.5
2.6	2000	1.15	557.2	"	"	16600	34000	3.1	1690	1.35
2.3	2000	1.25	621.5	<b>BK60G20-../D08MA4</b>	126	16600	34000	2.8	1610	1.55
1.9	2400	1.05	752.1	"	"	16600	34000	2.3	1960	1.3
1.6	2900	0.86	887.8	"	"	16600	34000	1.9	2400	1.05

## P = 0.55 кВт




50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
3.3	1590	3.3	432.1	<b>BK70Z-../D08MA4</b>	207	24100	50000	3.9	1340	3.9
2.8	1870	2.8	501.8	"	"	24100	50000	3.4	1540	3.4
2.5	2100	2.5	570.8	"	"	24100	50000	3.0	1750	3.0
2.2	2350	2.2	644.9	"	"	24100	50000	2.7	1940	2.7
2.0	2600	2.0	733.6	"	"	24100	50000	2.3	2250	2.3
1.7	2700	2.1	847.7	<b>BK70G20-../D08MA4</b>	205	24100	50000	2.0	2250	2.5
1.5	3050	1.85	964.6	"	"	24100	50000	1.8	2500	2.3
1.3	3600	1.6	1139	"	"	24100	50000	1.5	3050	1.85
1.1	4350	1.3	1280	"	"	24100	50000	1.4	3350	1.7
1.0	4800	1.2	1457	"	"	24100	50000	1.2	3900	1.45
1.1	3750	3.1	1307	<b>BK80G40-../D08MA4</b>	347	30000	75000	1.3	3000	3.8
1.0	4050	2.8	1425	"	"	30000	75000	1.2	3150	3.7
0.9	4600	2.5	1583	"	"	30000	75000	1.1	3550	3.2
0.8	5200	2.2	1775	"	"	30000	75000	0.95	4200	2.7
0.65	6600	1.75	2205	"	"	30000	75000	0.8	5100	2.3
0.6	7300	1.6	2449	"	"	30000	75000	0.7	6000	1.9
0.5	9000	1.3	2811	"	"	30000	75000	0.6	7200	1.6
0.45	10200	1.15	3120	"	"	30000	75000	0.55	8000	1.45
0.55	7400	2.5	2764	<b>BK90G50-../D08MA4</b>	620	49400	120000	0.65	5900	3.1
0.46	9300	2.0	3065	"	"	49400	120000	0.55	7400	2.5
0.39	11300	1.65	3672	"	"	49400	120000	0.46	9300	2.0
0.35	12900	1.45	4070	"	"	49400	120000	0.42	10300	1.8
0.29	16000	1.15	4952	"	"	49400	120000	0.34	13300	1.4
0.26	18000	1.05	5491	"	"	49400	120000	0.31	14800	1.25


## P = 0.75 кВт

50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
194	33.5	2.2	7.25	<b>BK06-../D08LA4</b>	16	790	-	235	28	2.6
145	45	1.8	9.71	"	"	880	-	174	37.5	2.1
120	54	1.5	11.67	"	"	930	-	144	45.5	1.75
92	70	1.15	15.29	"	"	1020	-	110	59	1.35
78	82	0.98	18.00	"	"	1080	-	94	68	1.2
65	99	0.81	21.54	"	"	1150	-	78	82	0.98
183	36	3.2	7.68	<b>BK10-../D08LA4</b>	28	2400	-	220	29.5	3.9
149	44	2.6	9.40	"	"	2700	-	179	36.5	3.2
118	55	2.1	11.93	"	"	3100	-	141	46.5	2.5
97	66	3.0	14.50	"	"	3900	-	116	55	3.6
83	77	1.75	16.92	"	"	3700	-	100	64	2.1
76	84	2.4	18.52	"	"	4300	-	91	70	2.9
62	103	1.95	22.65	"	"	4650	-	75	85	2.4
49	131	1.55	28.76	"	"	5200	-	59	109	1.85
41	157	1.25	34.25	"	"	5600	-	49.5	130	1.55
34.5	186	1.1	40.79	"	"	6000	-	41.5	155	1.3
29	215	0.93	48.96	"	"	6400	-	34.5	184	1.1
81	80	2.9	17.42	<b>BK20-../D08LA4</b>	38	3250	9000	97	67	3.4
58	111	3.0	24.29	"	"	4500	9000	70	92	3.6
49	131	2.5	28.66	"	"	4850	9000	59	109	3.0
38.5	167	2.0	36.69	"	"	5400	9000	46	140	2.4
33	195	1.7	42.70	"	"	5800	9000	39.5	163	2.0
27.5	230	1.45	51.22	"	"	6300	9000	33	193	1.7
23	275	1.2	61.30	"	"	6500	9000	27.5	230	1.45
18.5	340	0.97	76.79	"	"	7500	9000	22	285	1.15
16	385	0.86	88.12	"	"	8000	9000	19.5	315	1.05
42	153	2.9	33.70	<b>BK30-../D08LA4</b>	44	7000	12000	50	128	3.5
33	193	2.3	42.89	"	"	7800	12000	39.5	161	2.8
28	225	2.0	50.27	"	"	8300	12000	33.5	188	2.4
24	260	1.75	59.27	"	"	8900	12000	28.5	220	2.0

**P = 0.75 кВт**




50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
20	310	1.45	71.56	<b>BK30-../D08LA4</b>	"	9700	12000	23.5	265	1.7
16	380	1.2	88.38	"	"	10600	12000	19.5	315	1.45
14	430	1.05	102.4	"	"	11200	12000	16.5	365	1.25
11.5	520	0.87	123.9	<b>BK30Z-../D08LA4</b>	46	11200	12000	14	430	1.05
23.5	265	2.9	59.66	<b>BK40-../D08LA4</b>	64	9100	17000	28.5	220	3.5
20	310	2.5	70.11	"	"	9800	17000	24	255	3.1
17	365	2.1	84.36	"	"	10700	17000	20	310	2.5
13.5	450	1.75	104.0	"	"	11700	17000	16.5	365	2.1
12	500	1.55	118.2	<b>BK40Z-../D08LA4</b>	69	11700	17000	14.5	415	1.9
9.8	610	1.3	143.0	"	"	11700	17000	12	500	1.55
8.3	710	1.1	169.0	"	"	11700	17000	10	590	1.3
6.7	870	0.9	211.5	"	"	11700	17000	8.0	730	1.05
19	325	3.2	75.40	<b>BK50-../D08LA4</b>	93	12600	26000	22.5	275	3.8
15	410	2.6	95.29	"	"	14100	26000	18	340	3.1
12.5	485	2.2	115.4	<b>BK50Z-../D08LA4</b>	98	14100	26000	15	405	2.6
9.2	640	1.65	153.3	"	"	14100	26000	11	540	1.95
6.8	860	1.2	206.8	"	"	14100	26000	8.2	710	1.5
5.3	1090	0.96	264.5	"	"	14100	26000	6.4	900	1.15
9.2	770	3.0	153.7	<b>BK60Z-../D08LA4</b>	120	16600	34000	11	650	3.5
7.7	930	2.5	183.2	"	"	16600	34000	9.2	770	3.0
6.9	1030	2.2	205.0	"	"	16600	34000	8.2	870	2.6
5.9	1210	1.9	239.7	"	"	16600	34000	7.1	1000	2.3
5.3	1350	1.7	268.2	"	"	16600	34000	6.3	1130	2.0
4.5	1590	1.45	317.7	"	"	16600	34000	5.3	1350	1.7
4.0	1790	1.3	355.5	"	"	16600	34000	4.8	1490	1.55
3.5	2000	1.15	411.5	"	"	16600	34000	4.1	1740	1.3
3.1	2300	1.0	460.4	"	"	16600	34000	3.7	1930	1.2
2.9	2450	0.94	498.0	"	"	16600	34000	3.4	2100	1.1
2.6	2750	0.84	557.2	"	"	16600	34000	3.1	2300	1.0
2.3	2850	0.88	621.5	<b>BK60G20-../D08LA4</b>	128	16600	34000	2.8	2250	1.1
4.2	1700	3.1	333.6	<b>BK70Z-../D08LA4</b>	208	24100	50000	5.1	1400	3.7
3.7	1930	2.7	379.9	"	"	24100	50000	4.5	1590	3.3
3.3	2150	2.4	432.1	"	"	24100	50000	3.9	1830	2.8
2.8	2550	2.0	501.8	"	"	24100	50000	3.4	2100	2.5
2.5	2850	1.8	570.8	"	"	24100	50000	3.0	2350	2.2
2.2	3250	1.6	644.9	"	"	24100	50000	2.7	2650	1.95
2.0	3550	1.45	733.6	"	"	24100	50000	2.3	3100	1.7
1.7	3850	1.5	847.7	<b>BK70G20-../D08LA4</b>	206	24100	50000	2.0	3200	1.8
1.5	4350	1.3	964.6	"	"	24100	50000	1.8	3550	1.6
1.3	5000	1.15	1139	"	"	24100	50000	1.5	4300	1.35
1.1	6100	0.93	1280	"	"	24100	50000	1.4	4700	1.2
1.0	6700	0.85	1457	"	"	24100	50000	1.2	5500	1.05
1.5	3850	3.0	963.0	<b>BK80G40-../D08LA4</b>	348	30000	75000	1.8	3050	3.8
1.3	4450	2.6	1079	"	"	30000	75000	1.6	3450	3.3
1.1	5400	2.1	1307	"	"	30000	75000	1.3	4450	2.6
1.0	5900	1.95	1425	"	"	30000	75000	1.2	4750	2.4
0.9	6700	1.7	1583	"	"	30000	75000	1.1	5200	2.2
0.8	7600	1.5	1775	"	"	30000	75000	0.95	6200	1.85
0.65	9600	1.2	2205	"	"	30000	75000	0.8	7500	1.55
0.6	10400	1.1	2449	"	"	30000	75000	0.7	8700	1.3
0.9	6400	2.9	1579	<b>BK90G50-../D08LA4</b>	621	49400	120000	1.1	5000	3.7
0.8	7200	2.6	1803	"	"	49400	120000	0.95	5800	3.2
0.7	8300	2.2	2016	"	"	49400	120000	0.85	6500	2.8
0.55	10900	1.7	2764	"	"	49400	120000	0.65	8900	2.1
0.46	13400	1.4	3065	"	"	49400	120000	0.55	10900	1.7
0.39	16200	1.15	3672	"	"	49400	120000	0.46	13400	1.4
0.35	18300	1.0	4070	"	"	49400	120000	0.42	14900	1.25

**P = 1.1 кВт**


50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
320	30	3.2	4.44	<b>BK10-../D09SA4</b>	32	1890	-	380	25	3.8
235	41	2.6	6.02	"	"	2100	-	280	34.5	3.0
183	52	2.2	7.68	"	"	2400	-	220	43.5	2.6
149	64	1.8	9.40	"	"	2700	-	179	53	2.2
131	72	2.5	10.70	"	"	3500	-	158	59	3.1
118	81	1.4	11.93	"	"	3100	-	141	68	1.7
97	97	2.1	14.50	"	"	3900	-	116	81	2.5
83	113	1.2	16.92	"	"	3700	-	100	94	1.45
76	124	1.6	18.52	"	"	4300	-	91	103	1.95
62	152	1.3	22.65	"	"	4650	-	75	126	1.6
49	192	1.05	28.76	"	"	5200	-	59	160	1.25
41	230	0.87	34.25	"	"	5600	-	49.5	191	1.05
120	80	2.9	11.69	<b>BK20-../D09SA4</b>	42	2400	8800	144	67	3.4
95	99	3.3	14.75	"	"	3650	9000	114	82	4.0
81	118	1.95	17.42	"	"	3250	9000	97	98	2.4
73	129	2.6	19.39	"	"	4050	9000	87	108	3.1
58	163	2.0	24.29	"	"	4500	9000	70	135	2.4
49	192	1.7	28.66	"	"	4850	9000	59	160	2.1
38.5	245	1.35	36.69	"	"	5400	9000	46	205	1.6
33	285	1.15	42.70	"	"	5800	9000	39.5	235	1.4
27.5	335	0.99	51.22	"	"	6300	9000	33	280	1.2
23	405	0.81	61.30	"	"	6500	9000	27.5	335	0.99
68	140	2.3	20.85	<b>BK30-../D09SA4</b>	48	5000	12000	81	118	2.7
61	154	2.9	23.20	"	"	5900	12000	73	129	3.5
49	192	2.3	28.76	"	"	6500	12000	59	160	2.8
42	225	2.0	33.70	"	"	7000	12000	50	189	2.4
33	280	1.6	42.89	"	"	7800	12000	39.5	235	1.9
28	330	1.35	50.27	"	"	8300	12000	33.5	275	1.65
24	385	1.15	59.27	"	"	8900	12000	28.5	320	1.4
20	455	0.99	71.56	"	"	9700	12000	23.5	385	1.15
16	560	0.8	88.38	"	"	10600	12000	19.5	460	0.98
34.5	270	2.9	40.88	<b>BK40-../D09SA4</b>	68	7600	17000	41.5	225	3.5
27.5	335	2.3	51.18	"	"	8400	17000	33	280	2.8
23.5	390	2.0	59.66	"	"	9100	17000	28.5	320	2.4
20	455	1.7	70.11	"	"	9800	17000	24	380	2.1
17	530	1.45	84.36	"	"	10700	17000	20	455	1.7
13.5	660	1.2	104.0	"	"	11700	17000	16.5	540	1.45
12	740	1.05	118.2	<b>BK40Z-../D09SA4</b>	72	11700	17000	14.5	610	1.3
9.8	900	0.87	143.0	"	"	11700	17000	12	730	1.05
29.5	315	3.3	47.50	<b>BK50-../D09SA4</b>	96	10100	25700	35.5	260	4.0
23.5	390	2.7	60.76	"	"	11400	26000	28	330	3.2
19	480	2.2	75.40	"	"	12600	26000	22.5	405	2.6
15	600	1.75	95.29	"	"	14100	26000	18	500	2.1
12.5	710	1.5	115.4	<b>BK50Z-../D09SA4</b>	101	14100	26000	15	590	1.8
9.2	940	1.1	153.3	"	"	14100	26000	11	790	1.35
6.8	1260	0.83	206.8	"	"	14100	26000	8.2	1050	1.0
14	750	3.1	101.2	<b>BK60-../D09SA4</b>	105	13900	34000	17	610	3.8
12.5	840	2.7	113.2	"	"	15000	34000	15	700	3.3
11.5	910	2.5	122.5	"	"	15500	34000	14	750	3.1
10.5	1000	2.3	137.0	"	"	16600	34000	12.5	840	2.7
9.2	1140	2.0	153.7	<b>BK60Z-../D09SA4</b>	124	16600	34000	11	950	2.4
7.7	1360	1.7	183.2	"	"	16600	34000	9.2	1140	2.0
6.9	1520	1.5	205.0	"	"	16600	34000	8.2	1280	1.8
5.9	1780	1.3	239.7	"	"	16600	34000	7.1	1470	1.55
5.3	1980	1.15	268.2	"	"	16600	34000	6.3	1660	1.4
4.5	2300	1.0	317.7	"	"	16600	34000	5.3	1980	1.15
4.0	2600	0.88	355.5	"	"	16600	34000	4.8	2150	1.05
6.2	1690	3.1	226.2	<b>BK70Z-../D09SA4</b>	212	24100	50000	7.5	1400	3.7
5.5	1910	2.7	257.3	"	"	24100	50000	6.6	1590	3.3
4.8	2150	2.4	293.3	"	"	24100	50000	5.8	1810	2.9

## P = 1.1 кВт




50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
4.2	2500	2.1	333.6	BK70Z-../D09SA4	"	24100	50000	5.1	2050	2.5
3.7	2800	1.85	379.9	"	"	24100	50000	4.5	2300	2.3
3.3	3150	1.65	432.1	"	"	24100	50000	3.9	2650	1.95
2.8	3750	1.4	501.8	"	"	24100	50000	3.4	3050	1.7
2.5	4200	1.25	570.8	"	"	24100	50000	3.0	3500	1.5
2.2	4750	1.1	644.9	"	"	24100	50000	2.7	3850	1.35
2.0	5200	1.0	733.6	"	"	24100	50000	2.3	4550	1.15
1.7	5800	0.98	847.7	BK70G20-../D09SA4	210	24100	50000	2.0	4850	1.2
1.5	6500	0.88	964.6	"	"	24100	50000	1.8	5400	1.05
2.9	3600	3.2	499.5	BK80Z-../D09SA4	341	30000	75000	3.4	3050	3.8
2.6	4000	2.9	559.5	"	"	30000	75000	3.1	3350	3.4
2.4	3600	3.2	607.8	BK80G40-../D09SA4	352	30000	75000	2.8	3000	3.8
2.1	4150	2.8	680.9	"	"	30000	75000	2.5	3350	3.4
1.9	4700	2.4	756.3	"	"	30000	75000	2.3	3700	3.1
1.7	5200	2.2	847.2	"	"	30000	75000	2.0	4300	2.7
1.5	6100	1.9	963.0	"	"	30000	75000	1.8	4900	2.3
1.3	7000	1.65	1079	"	"	30000	75000	1.6	5500	2.1
1.1	8500	1.35	1307	"	"	30000	75000	1.3	7000	1.65
1.0	9300	1.25	1425	"	"	30000	75000	1.2	7500	1.55
0.9	10400	1.1	1583	"	"	30000	75000	1.1	8300	1.4
1.4	6100	3.0	1008	BK90G50-../D09SA4	625	49400	120000	1.7	4800	3.9
1.3	6500	2.8	1127	"	"	49400	120000	1.5	5400	3.4
1.1	8300	2.2	1363	"	"	49400	120000	1.3	6800	2.7
0.9	10100	1.85	1579	"	"	49400	120000	1.1	8000	2.3
0.8	11400	1.6	1803	"	"	49400	120000	0.95	9300	2.0
0.7	13000	1.4	2016	"	"	49400	120000	0.85	10400	1.8
0.55	16900	1.1	2764	"	"	49400	120000	0.65	14000	1.3

## P = 1.5 кВт

50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
320	41	2.3	4.44	BK10-../D09LA4	36	1890	-	380	34.5	2.8
235	56	1.9	6.02	"	"	2100	-	280	47	2.2
183	72	1.6	7.68	"	"	2400	-	220	59	1.95
149	88	1.3	9.40	"	"	2700	-	179	73	1.6
131	98	1.85	10.70	"	"	3500	-	158	81	2.2
118	111	1.05	11.93	"	"	3100	-	141	93	1.25
97	132	1.5	14.50	"	"	3900	-	116	111	1.8
83	155	0.88	16.92	"	"	3700	-	100	128	1.05
76	169	1.2	18.52	"	"	4300	-	91	141	1.4
62	205	0.98	22.65	"	"	4650	-	75	171	1.15
177	74	3.1	7.91	BK20-../D09LA4	46	1330	7600	215	61	3.8
142	92	2.5	9.91	"	"	1910	8300	170	77	3.0
126	102	3.0	11.14	"	"	3300	8100	151	85	3.5
120	109	2.1	11.69	"	"	2400	8800	144	91	2.5
95	135	2.4	14.75	"	"	3650	9000	114	113	2.9
81	160	1.45	17.42	"	"	3250	9000	97	134	1.7
73	176	1.9	19.39	"	"	4050	9000	87	148	2.2
58	220	1.5	24.29	"	"	4500	9000	70	184	1.8
49	260	1.25	28.66	"	"	4850	9000	59	215	1.55
38.5	330	1.0	36.69	"	"	5400	9000	46	280	1.2
33	390	0.85	42.70	"	"	5800	9000	39.5	325	1.0
118	111	2.9	11.93	BK30-../D09LA4	52	3650	12000	141	93	3.4
101	129	2.5	13.98	"	"	4050	12000	121	107	3.0
78	165	2.7	17.95	"	"	5300	12000	94	137	3.3
68	191	1.7	20.85	"	"	5000	12000	81	160	2.0
61	210	2.1	23.20	"	"	5900	12000	73	176	2.6
49	260	1.75	28.76	"	"	6500	12000	59	215	2.1
42	305	1.5	33.70	"	"	7000	12000	50	255	1.75
33	385	1.15	42.89	"	"	7800	12000	39.5	320	1.4


P = 1.5 кВт



50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
28	450	1.0	50.27	<b>BK30-../D09LA4</b>	"	8300	12000	33.5	375	1.2
24	520	0.87	59.27	"	"	8900	12000	28.5	440	1.0
49	260	3.0	28.59	<b>BK40-../D09LA4</b>	72	6300	17000	59	215	3.6
40.5	315	2.5	34.61	"	"	6900	17000	49	260	3.0
34.5	370	2.1	40.88	"	"	7600	17000	41.5	310	2.5
27.5	455	1.7	51.18	"	"	8400	17000	33	380	2.1
23.5	530	1.45	59.66	"	"	9100	17000	28.5	440	1.75
20	620	1.25	70.11	"	"	9800	17000	24	510	1.55
17	730	1.05	84.36	"	"	10700	17000	20	620	1.25
13.5	900	0.87	104.0	"	"	11700	17000	16.5	730	1.05
40	320	3.3	35.21	<b>BK50-../D09LA4</b>	100	8700	23100	48	265	4.0
29.5	430	2.4	47.50	"	"	10100	25700	35.5	355	3.0
23.5	530	2.0	60.76	"	"	11400	26000	28	450	2.3
19	650	1.6	75.40	"	"	12600	26000	22.5	550	1.9
15	820	1.3	95.29	"	"	14100	26000	18	680	1.55
12.5	970	1.1	115.4	<b>BK50Z-../D09LA4</b>	105	14100	26000	15	810	1.3
9.2	1290	0.81	153.3	"	"	14100	26000	11	1080	0.97
18	790	2.9	78.13	<b>BK60-../D09LA4</b>	109	11900	34000	22	650	3.5
16.5	860	2.7	87.41	"	"	12900	34000	19.5	730	3.2
14	1020	2.3	101.2	"	"	13900	34000	17	840	2.7
12.5	1140	2.0	113.2	"	"	15000	34000	15	950	2.4
11.5	1240	1.85	122.5	"	"	15500	34000	14	1020	2.3
10.5	1360	1.7	137.0	"	"	16600	34000	12.5	1140	2.0
9.2	1550	1.5	153.7	<b>BK60Z-../D09LA4</b>	128	16600	34000	11	1300	1.75
7.7	1860	1.25	183.2	"	"	16600	34000	9.2	1550	1.5
6.9	2050	1.1	205.0	"	"	16600	34000	8.2	1740	1.3
5.9	2400	0.96	239.7	"	"	16600	34000	7.1	2000	1.15
5.3	2700	0.85	268.2	"	"	16600	34000	6.3	2250	1.0
9.1	1570	3.3	154.4	<b>BK70-../D09LA4</b>	195	21900	50000	11	1300	4.0
8.0	1790	2.9	175.7	"	"	24100	50000	9.6	1490	3.5
7.4	1930	2.7	190.4	<b>BK70Z-../D09LA4</b>	216	24100	50000	8.9	1600	3.3
6.2	2300	2.3	226.2	"	"	24100	50000	7.5	1910	2.7
5.5	2600	2.0	257.3	"	"	24100	50000	6.6	2150	2.4
4.8	2950	1.75	293.3	"	"	24100	50000	5.8	2450	2.1
4.2	3400	1.55	333.6	"	"	24100	50000	5.1	2800	1.85
3.7	3850	1.35	379.9	"	"	24100	50000	4.5	3150	1.65
3.3	4300	1.2	432.1	"	"	24100	50000	3.9	3650	1.4
2.8	5100	1.0	501.8	"	"	24100	50000	3.4	4200	1.25
2.5	5700	0.91	570.8	"	"	24100	50000	3.0	4750	1.1
2.2	6500	0.8	644.9	"	"	24100	50000	2.7	5300	0.98
3.6	3950	2.9	389.0	<b>BK80Z-../D09LA4</b>	345	30000	75000	4.4	3250	3.5
3.3	4300	2.7	435.7	"	"	30000	75000	3.9	3650	3.2
2.9	4900	2.3	499.5	"	"	30000	75000	3.4	4200	2.7
2.6	5500	2.1	559.5	"	"	30000	75000	3.1	4600	2.5
2.4	5200	2.2	607.8	<b>BK80G40-../D09LA4</b>	356	30000	75000	2.8	4350	2.6
2.1	5900	1.95	680.9	"	"	30000	75000	2.5	4850	2.4
1.9	6700	1.7	756.3	"	"	30000	75000	2.3	5400	2.1
1.7	7500	1.55	847.2	"	"	30000	75000	2.0	6200	1.85
1.5	8600	1.35	963.0	"	"	30000	75000	1.8	7000	1.65
1.3	10000	1.15	1079	"	"	30000	75000	1.6	7900	1.45
1.1	12000	0.96	1307	"	"	30000	75000	1.3	10000	1.15
1.0	13100	0.88	1425	"	"	30000	75000	1.2	10700	1.05
2.2	6500	2.8	637.7	<b>BK90Z-../D09LA4</b>	618	49400	120000	2.7	5300	3.5
2.0	7100	2.6	713.5	"	"	49400	120000	2.4	5900	3.1
1.8	6600	2.8	821.0	<b>BK90G50-../D09LA4</b>	629	49400	120000	2.1	5400	3.4
1.6	7700	2.4	882.3	"	"	49400	120000	2.0	5900	3.1
1.4	8800	2.1	1008	"	"	49400	120000	1.7	7000	2.6
1.3	9500	1.95	1127	"	"	49400	120000	1.5	8000	2.3
1.1	11800	1.55	1363	"	"	49400	120000	1.3	9800	1.9
0.9	14400	1.3	1579	"	"	49400	120000	1.1	11500	1.6
0.8	16100	1.15	1803	"	"	49400	120000	0.95	13300	1.4




**P = 2.2 кВт**



50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
320	60	1.6	4.44	<b>BK10-../D09XA4</b>	40	1890	-	380	50	1.9
235	82	1.3	6.02	"	"	2100	-	280	69	1.5
183	105	1.1	7.68	"	"	2400	-	220	87	1.3
149	129	0.89	9.40	"	"	2700	-	179	107	1.05
131	144	1.25	10.70	"	"	3500	-	158	119	1.5
97	194	1.05	14.50	"	"	3900	-	116	163	1.25
76	245	0.82	18.52	"	"	4300	-	91	205	0.98
310	62	3.2	4.54	<b>BK20-../D09XA4</b>	50	520	6100	375	51	3.8
235	82	2.7	6.02	"	"	580	6800	280	69	3.2
177	109	2.1	7.91	"	"	1330	7600	215	89	2.6
142	136	1.7	9.91	"	"	1910	8300	170	113	2.0
126	150	2.0	11.14	"	"	3300	8100	151	125	2.4
120	161	1.45	11.69	"	"	2400	8800	144	134	1.7
95	199	1.65	14.75	"	"	3650	9000	114	165	2.0
81	235	0.98	17.42	"	"	3250	9000	97	197	1.15
73	255	1.3	19.39	"	"	4050	9000	87	215	1.55
58	325	1.0	24.29	"	"	4500	9000	70	270	1.2
49	385	0.86	28.66	"	"	4850	9000	59	320	1.05
300	64	3.0	4.73	<b>BK30-../D09XA4</b>	56	1550	8800	360	53	3.7
235	82	2.6	6.02	"	"	1690	9600	280	69	3.1
188	102	2.6	7.45	"	"	2200	10400	230	84	3.2
146	132	2.4	9.63	"	"	3150	11500	175	110	2.9
123	153	2.7	11.39	"	"	4150	11000	148	127	3.3
118	163	1.95	11.93	"	"	3650	12000	141	137	2.3
101	189	1.7	13.98	"	"	4050	12000	121	158	2.0
97	194	2.3	14.50	"	"	4900	12000	116	163	2.8
78	240	1.9	17.95	"	"	5300	12000	94	200	2.3
68	280	1.15	20.85	"	"	5000	12000	81	235	1.35
61	305	1.5	23.20	"	"	5900	12000	73	255	1.75
49	385	1.15	28.76	"	"	6500	12000	59	320	1.4
42	450	1.0	33.70	"	"	7000	12000	50	375	1.2
33	560	0.8	42.89	"	"	7800	12000	39.5	470	0.96
119	162	3.0	11.86	<b>BK40-../D09XA4</b>	76	1770	12200	142	136	3.6
78	240	3.3	18.05	"	"	4900	15300	94	200	3.9
63	300	2.6	22.44	"	"	5500	16500	75	250	3.1
49	385	2.0	28.59	"	"	6300	17000	59	320	2.4
40.5	465	1.7	34.61	"	"	6900	17000	49	385	2.0
34.5	540	1.45	40.88	"	"	7600	17000	41.5	455	1.7
27.5	670	1.15	51.18	"	"	8400	17000	33	560	1.4
23.5	780	1.0	59.66	"	"	9100	17000	28.5	640	1.2
20	910	0.86	70.11	"	"	9800	17000	24	760	1.05
79	240	3.0	17.92	<b>BK50-../D09XA4</b>	104	4600	16800	94	200	3.6
53	355	3.0	26.51	"	"	7800	21200	64	295	3.6
40	470	2.2	35.21	"	"	8700	23100	48	390	2.7
29.5	630	1.65	47.50	"	"	10100	25700	35.5	520	2.0
23.5	780	1.35	60.76	"	"	11400	26000	28	660	1.6
19	960	1.1	75.40	"	"	12600	26000	22.5	810	1.3
15	1200	0.88	95.29	"	"	14100	26000	18	1000	1.05
28	750	3.1	50.40	<b>BK60-../D09XA4</b>	113	9100	29800	33.5	620	3.7
24	870	2.6	58.95	"	"	9900	31500	28.5	730	3.2
21.5	970	2.4	65.95	"	"	10900	33000	25.5	820	2.8
18	1160	2.0	78.13	"	"	11900	34000	22	950	2.4
16.5	1270	1.8	87.41	"	"	12900	34000	19.5	1070	2.1
14	1500	1.55	101.2	"	"	13900	34000	17	1230	1.85
12.5	1680	1.35	113.2	"	"	15000	34000	15	1400	1.65
11.5	1820	1.25	122.5	"	"	15500	34000	14	1500	1.55
10.5	2000	1.15	137.0	"	"	16600	34000	12.5	1680	1.35
9.2	2250	1.0	153.7	<b>BK60Z-../D09XA4</b>	132	16600	34000	11	1910	1.2
7.7	2700	0.85	183.2	"	"	16600	34000	9.2	2250	1.0
12	1750	3.0	120.2	<b>BK70-../D09XA4</b>	199	18600	50000	14	1500	3.5
10.5	2000	2.6	136.7	"	"	20700	50000	12.5	1680	3.1

## P = 2.2 кВт




50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
9.1	2300	2.3	154.4	BK70-../D09XA4	"	21900	50000	11	1910	2.7
8.0	2600	2.0	175.7	"	"	24100	50000	9.6	2150	2.4
7.4	2800	1.85	190.4	BK70Z-../D09XA4	220	24100	50000	8.9	2350	2.2
6.2	3350	1.55	226.2	"	"	24100	50000	7.5	2800	1.85
5.5	3800	1.35	257.3	"	"	24100	50000	6.6	3150	1.65
4.8	4350	1.2	293.3	"	"	24100	50000	5.8	3600	1.45
4.2	5000	1.05	333.6	"	"	24100	50000	5.1	4100	1.25
3.7	5600	0.93	379.9	"	"	24100	50000	4.5	4650	1.1
3.3	6300	0.83	432.1	"	"	24100	50000	3.9	5300	0.98
5.6	3750	3.1	253.3	BK80Z-../D09XA4	349	30000	75000	6.7	3100	3.7
4.7	4450	2.6	300.6	"	"	30000	75000	5.6	3750	3.1
4.2	5000	2.3	336.7	"	"	30000	75000	5.0	4200	2.7
3.6	5800	2.0	389.0	"	"	30000	75000	4.4	4750	2.4
3.3	6300	1.85	435.7	"	"	30000	75000	3.9	5300	2.2
2.9	7200	1.6	499.5	"	"	30000	75000	3.4	6100	1.9
2.6	8000	1.45	559.5	"	"	30000	75000	3.1	6700	1.7
2.4	8000	1.45	607.8	BK80G40-../D09XA4	360	30000	75000	2.8	6700	1.7
2.1	9100	1.25	680.9	"	"	30000	75000	2.5	7500	1.55
1.9	10200	1.15	756.3	"	"	30000	75000	2.3	8300	1.4
1.7	11400	1.0	847.2	"	"	30000	75000	2.0	9500	1.2
1.5	13100	0.88	963.0	"	"	30000	75000	1.8	10700	1.05
3.6	5800	3.2	389.1	BK90Z-../D09XA4	622	49400	120000	4.4	4750	3.9
3.3	6300	2.9	435.3	"	"	49400	120000	3.9	5300	3.5
2.9	7200	2.6	499.2	"	"	49400	120000	3.4	6100	3.0
2.6	8000	2.3	558.5	"	"	49400	120000	3.1	6700	2.8
2.2	9500	1.95	637.7	"	"	49400	120000	2.7	7700	2.4
2.0	10500	1.75	713.5	"	"	49400	120000	2.4	8700	2.1
1.8	10300	1.8	821.0	BK90G50-../D09XA4	633	49400	120000	2.1	8600	2.2
1.6	11900	1.55	882.3	"	"	49400	120000	2.0	9300	2.0
1.4	13600	1.35	1008	"	"	49400	120000	1.7	11000	1.7
1.3	14600	1.25	1127	"	"	49400	120000	1.5	12400	1.5
1.1	17800	1.05	1363	"	"	49400	120000	1.3	14900	1.25

## P = 3 кВт

50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
305	86	2.3	4.73	BK30-../D11SA4	59	1550	8800	365	72	2.7
240	109	1.95	6.02	"	"	1690	9600	285	92	2.3
191	138	1.95	7.45	"	"	2200	10400	230	114	2.4
148	178	1.8	9.63	"	"	3150	11500	178	148	2.2
125	205	2.0	11.39	"	"	4150	11000	151	170	2.4
120	215	1.5	11.93	"	"	3650	12000	144	183	1.75
102	255	1.25	13.98	"	"	4050	12000	123	210	1.5
98	260	1.75	14.50	"	"	4900	12000	118	215	2.1
80	320	1.4	17.95	"	"	5300	12000	96	265	1.7
62	415	1.1	23.20	"	"	5900	12000	74	345	1.3
49.5	520	0.87	28.76	"	"	6500	12000	60	425	1.05
153	172	2.9	9.31	BK40-../D11SA4	84	1040	11200	184	143	3.4
120	215	2.3	11.86	"	"	1770	12200	145	181	2.7
98	260	3.0	14.50	"	"	4500	14300	118	215	3.6
79	325	2.4	18.05	"	"	4900	15300	95	270	2.9
64	400	1.95	22.44	"	"	5500	16500	77	330	2.4
50	510	1.55	28.59	"	"	6300	17000	60	425	1.85
41.5	620	1.25	34.61	"	"	6900	17000	49.5	520	1.5
35	730	1.05	40.88	"	"	7600	17000	42	610	1.3
80	325	2.2	17.92	BK50-../D11SA4	114	4600	16800	96	270	2.7
74	345	3.0	19.33	"	"	6900	19200	89	285	3.7
54	475	2.2	26.51	"	"	7800	21200	65	395	2.7
40.5	630	1.65	35.21	"	"	8700	23100	49	520	2.0



**P = 3 кВт**



50 Гц			i	Тип	m	F <sub>RN</sub>	F <sub>RV</sub>	60 Гц		
n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>						n <sub>2</sub> 1/min	M <sub>2</sub> Нм	f <sub>B</sub>
30	840	1.25	47.50	<b>BK50-../D11SA4</b>	"	10100	25700	36	700	1.5
23.5	1070	0.98	60.76	"	"	11400	26000	28.5	880	1.2
19	1310	0.8	75.40	"	"	12600	26000	23	1080	0.97
38	750	3.1	37.80	<b>BK60-../D11SA4</b>	124	7300	26500	45.5	620	3.7
32	890	2.6	45.05	"	"	8200	28300	38	750	3.1
28.5	1000	2.3	50.40	"	"	9100	29800	34	840	2.7
24.5	1160	2.0	58.95	"	"	9900	31500	29.5	970	2.4
22	1300	1.75	65.95	"	"	10900	33000	26	1100	2.1
18.5	1540	1.5	78.13	"	"	11900	34000	22	1300	1.75
16.5	1730	1.35	87.41	"	"	12900	34000	20	1430	1.6
14.5	1970	1.15	101.2	"	"	13900	34000	17	1680	1.35
13	2200	1.05	113.2	"	"	15000	34000	15.5	1840	1.25
12	2350	0.98	122.5	"	"	15500	34000	14	2000	1.15
10.5	2700	0.85	137.0	"	"	16600	34000	12.5	2250	1.0
18	1590	3.3	79.89	<b>BK70-../D11SA4</b>	203	14300	47600	21.5	1330	3.9
16	1790	2.9	90.96	"	"	15300	49900	19	1500	3.5
14	2000	2.6	103.5	"	"	17200	50000	17	1680	3.1
12	2350	2.2	120.2	"	"	18600	50000	14.5	1970	2.6
10.5	2700	1.95	136.7	"	"	20700	50000	13	2200	2.4
9.2	3100	1.7	154.4	"	"	21900	50000	11.5	2450	2.1
8.1	3500	1.5	175.7	"	"	24100	50000	9.8	2900	1.8
7.5	3800	1.35	190.4	<b>BK70Z-../D11SA4</b>	230	24100	50000	9.0	3150	1.65
6.3	4500	1.15	226.2	"	"	24100	50000	7.6	3750	1.4
5.6	5100	1.0	257.3	"	"	24100	50000	6.7	4250	1.2
4.9	5800	0.9	293.3	"	"	24100	50000	5.9	4850	1.05
8.3	3450	3.0	171.5	<b>BK80-../D11SA4</b>	318	30000	75000	10	2850	3.7
8.0	3550	3.2	177.6	<b>BK80Z-../D11SA4</b>	360	30000	75000	9.7	2950	3.9
7.2	3950	2.9	198.9	"	"	30000	75000	8.6	3300	3.5
6.3	4500	2.6	226.1	"	"	30000	75000	7.6	3750	3.1
5.7	5000	2.3	253.3	"	"	30000	75000	6.8	4200	2.7
4.8	5900	1.95	300.6	"	"	30000	75000	5.7	5000	2.3
4.3	6600	1.75	336.7	"	"	30000	75000	5.1	5600	2.1
3.7	7700	1.5	389.0	"	"	30000	75000	4.4	6500	1.75
3.3	8600	1.35	435.7	"	"	30000	75000	4.0	7100	1.6
2.9	9800	1.15	499.5	"	"	30000	75000	3.5	8100	1.4
2.6	11000	1.05	559.5	"	"	30000	75000	3.1	9200	1.25
2.4	11100	1.05	607.8	<b>BK80G40-../D11SA4</b>	368	30000	75000	2.9	9100	1.25
2.1	12800	0.9	680.9	"	"	30000	75000	2.6	10100	1.15
1.9	14200	0.81	756.3	"	"	30000	75000	2.3	11600	0.99
4.9	5800	3.2	295.6	<b>BK90Z-../D11SA4</b>	626	49400	120000	5.8	4900	3.8
4.3	6600	2.8	330.7	"	"	49400	120000	5.2	5500	3.4
3.7	7700	2.4	389.1	"	"	49400	120000	4.4	6500	2.8
3.3	8600	2.2	435.3	"	"	49400	120000	4.0	7100	2.6
2.9	9800	1.9	499.2	"	"	49400	120000	3.5	8100	2.3
2.6	11000	1.7	558.5	"	"	49400	120000	3.1	9200	2.0
2.3	12400	1.5	637.7	"	"	49400	120000	2.7	10600	1.75
2.0	14300	1.3	713.5	"	"	49400	120000	2.4	11900	1.55
1.8	14500	1.3	821.0	<b>BK90G50-../D11SA4</b>	642	49400	120000	2.1	12300	1.5
1.7	15600	1.2	882.3	"	"	49400	120000	2.0	13100	1.4
1.5	17700	1.05	1008	"	"	49400	120000	1.7	15500	1.2
1.3	20500	0.9	1127	"	"	49400	120000	1.6	16300	1.15